



Brand: Axor, Germany

Name: ShowerSolutions Overhead Shower

240/240 with Ceiling Connection

Item Code: 10929.000

Designer: Philippe Starck

Color / Finish: Chrome

Dimensions: Shower head size: 240 x 240 mm

## Product info:

Consists of overhead shower, ceiling connector

· Spray type: Rain Air

• Flow rate RainAir spray (at 3 bar): 12 l/min

• Flow rate expansible to 25 l/min

· Material spray disc: metal

· Spray disc removable for cleaning

· Brass ceiling connector

• Ceiling connection length: 102 mm

Installation: ceiling

• Connection thread G ½

Connection dimension: DN15

• Not suitable for continuous flow water heaters



## 120 / 120 - | - 68 - | - 68 - | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | - 78 1/2 | -


## Technology







## **Flowchart**



The consumption was measured in combination with the appropriate fittings (thermostat/mixer/in-wall valve) to reflect actual application in practice.

Follow cleaning instructions and avoid using any harmful chemicals.

All information is for reference only. Installation shall always be based on the specs provided with actual delivered items. For more info, visit **www.kuysen.com**