



- Consists of overhead shower, ceiling connector
- Spray type: Rain
- FlexPower: nozzles automatically adjust to water pressure by opening and closing
- QuickClean+: reduce limescale deposits thanks to the elasticity of the nozzles
- Flow rate Rain spray at 3 bar: 7,4 l/min
- Function from: 5,7 l/min
- Maximum flow rate at 3 bar: 7,4 l/min
- Minimum flow pressure: 1,3 bar
- Overhead shower angle adjustable
- Material spray disc: metal
- Spray disc removable for cleaning
- Metal ceiling connector
- Ceiling connection length: 100 mm
- Installation: ceiling mounting
- Connection thread: G ½

The graph shows the pressure-flow characteristic of a pump. The x-axis represents flow rate Q in l/min (0 to 30) and l/sec (0 to 0.5). The y-axis represents pressure in MPa (0.00 to 0.60) and bar (0.0 to 6.0). The curve starts at the origin (0,0), rises to a peak at $Q \approx 8 \text{ l/min}$ and $P \approx 0.30 \text{ MPa}$, and then drops sharply.

Follow cleaning instructions and avoid using any harmful chemicals. Failure to do so voids the warranty
All information is for reference only. Installation shall always be based on the specs provided with actual delivered items.
For more info, visit **www.kuysen.com**