

> CATALOGUE 2016

The SIAMP logo, featuring the letters "SIAMP" in a bold, white, sans-serif font against a dark blue background. A stylized blue wave or swoosh is positioned between the "I" and "A".

Sanitary expertise
& water friendly



- > Wall frames
- > Concealed cisterns
- > Flushing options
- > Wall hung accessories
- > Technical equipment
- > Toilet seats



SIAMP Ltd, Unit C2, Meadowbank Business Park,
Tweedale Way, Hollinwood, Oldham, Greater Manchester, OL9 8EH
T: 0161 681 2120 F: 0161 681 2130 W: www.siamp.co.uk
Enquiries: info@siamp.co.uk Technical support: aftersales@siamp.co.uk

Sanitary expertise
& water friendly



SIAMP, the constantly evolving specialist

Founded in 1947, SIAMP is a world leader in the design, manufacture and distribution of sanitary equipment. SIAMP has been innovating the sanitary industry for nearly 70 years with commitment to research and development. SIAMP continues to dominate the market with innovative technical solutions developing efficient equipment which guarantees hygiene and comfort with responsible water management.

A major player in the sanitary equipment market, SIAMP is continually striving to improve the viability, the efficiency and the design of its products. Toilet seats, wall frames, concealed cisterns, flush valves & inlet valves, SIAMP designs, manufactures and distributes a large range of products and systems for toilet equipment.

Worldwide partner to many of the major ceramic manufacturers and a comprehensive distribution network, SIAMP is in constant touch with this ever-evolving market. Understanding the markets requirements, with focus on sustainable development, SIAMP is therefore a source of innovations, supported by a large number of international patents.



Sanitary expertise
& water friendly

SIAMP, from design to manufacturing



SIAMP highlights two major areas of its research and development :


- > Products that guarantee hygiene and comfort.
- > Responsible water management.

SIAMP designs and develops solutions that bring advanced technology and innovation.

SIAMP guarantees its product performance as well as environmental respect.

In this catalogue, you will find creative solutions for the following:

- water saving
- dry riser
- bacteria free
- inclusive design products
- acoustic comfort
- ease of installation



As well as its factory and headquarters in Monaco, SIAMP has a worldwide presence with subsidiaries located in United Kingdom, Germany and Russia. Production plants with commercial offices are also located in Turkey, Vietnam, India and more recently Brazil.


> Our solutions

> To suit all installation needs



> Water saving and Delayed Action:

Save up to 5 litres of water per day



> 95L Delayed action available in...



> 99B Delayed action available in...




For more information:
Web: siamp.co.uk

> **WC pack Deluxe Samoa**
Space saving, water saving



> **Attractive:**
Aesthetic design



> **99 range**



> **99 inlet presents a wide range of features, meeting your needs**

These NF & WRAS certified inlet valves are available with the following:

- a 1/2" plastic connection
- a 1/2" brass connection
- a telescopic tube 1/2" connection to reach high water level
- a water saving function available as an option on the inlet valve


> Toilet seats range

> Various materials of toilet seats

- **Thermoplastic:** low cost, hard wearing and recyclable material.
- **Thermoset:** heavy duty, quality material. It is antibacterial and scratch-resistant.
- **MDF:** medium-density fiberboard, presents the aesthetics and warmth of wood.
- **Composite wood:** the most robust material, dedicated to high-end products, offering a high quality finish.

> Hinge options

- **PREMIUM:** Quick fitting, soft close and detachable. Designed for both comfort and hygiene.
- **CLASSIC:** Products intended for intensive use, especially in commercial projects.



> Various shapes and design



For more information:
Web: siamp.co.uk

> Contents

WALL HUNG SOLUTIONS

BCM 790	14
BCM 800	17
BCM - BCU 350	18
BLM 400	19 - 20
SCU 350	21

WC PACKS

Deluxe Samoa	22
Standard Samoa	24
	25

CONCEALED CISTERNS

Flush plate operated cistern	26
Button operated cisterns	29
	30

FLUSHING OPTIONS

36

WALL HUNG ACCESSORIES

56

TECHNICAL EQUIPMENT

58

Inlet valves	62
Flush valves	69

TOILET SEATS

74

Composite wood / MDF	77
Thermoset	80
Thermoplastic	83

MEASURES, WEIGHTS AND PRESSURE CONVERSION TABLE

88

Index	89
-------	----



> WALL FRAMES / INTRODUCTION

Wall frames

Concealed cisterns

Flushing options

Wall hung accessories

Technical equipment

Toilet seats



> WALL FRAMES

Contents

■ Wall hung solutions

Wall frame BCM 790: <i>Low height - Front flush plate</i>	17
Wall frame BCM 800: <i>Low height - Top flush plate</i>	18
Wall frame BCM - BCU 350: <i>Narrow - Front flush plate</i>	19-20
Wall frames for washbasins & bidets	21

■ WC packs

Deluxe Samoa	24
Standard Samoa	25

The range of SIAMP supporting frames makes it possible to install wall hung equipment safely and easily: WC's, washbasins and bidets. The different configurations allow you to fit out bathrooms or cloakrooms as you want. The SIAMP products are WRAS and/or NF certified or designed and manufactured to conform to these standards.

• WATER SAVING:

A water saving delayed action inlet valve comes as a standard with all our WC frames. They can also be adjusted to a 4 litre full flush.

• CHOICE:

The extended range of SIAMP flush plates meets the various needs of the user. Appealing materials such as glass or metal are available.

• FLUSH EFFICIENCY:

SIAMP conforms to WRAS flushing standards for the incorporated fittings and each of the cisterns complies with the European Norm 14055 Class 2. This ensures long term reliability and flush efficiency.

> Installation advices

> The wall frames advantages



Unlike certain preconceptions, a wall hung WC can be installed in almost any situation.

Only very poor quality floors require specific installation, although it is not totally impossible.

The overall dimensions of the frame plus WC are no deeper than a conventional toilet and may even generate space saving if the frame is incorporated into the wall.

Installing a wall hung WC means choosing an installation that is...

...better looking: Offering a real possibility of improving the decorative scheme of the WC

...more hygienic: The concealed cistern and wall hung WC eliminate hidden corners, simplify cleaning and are in favor of perfect hygiene.

> Floor and wall types relations with SIAMP models:

Model	Supporting wall	Light partition
Non supporting floor	BCM (wall fixing)	
	BCU (self supporting with wall fixing)	
Supporting floor	BCU (self supporting)	BCU (self supporting)

> Where can a wall hung WC be installed?

A wall hung bowl can be installed in a toilet area instead of a back to wall, close coupled or high level WC and cistern.

> What needs to be known before choosing models?

I – Floor type:

- Is the wall hung frame to be fixed to a concrete screed or another known finished floor type.

II – Wall type:

- A supporting wall is structurally strong and is used to support the building. It can be an internal or external wall often 100mm or greater.
- Partition wall is a non-supporting wall used for separating rooms or distributing utilities. Partition walls are usually made from lightweight bricks, plasterboard or any other material less than 100mm thick.







BCM (wall fixing):



BCU (self supporting and/or wall fixing):




> Wall frame selection

	BCM 790	BCM 800	BCM 350	BCU 350	BLM 400	SCU 350
WALL FRAMES						
Wall frame type						
Wall frame with concealed cistern	•	•	•	•		
WC	•	•	•	•		•
Washbasin					•	
Bidet						•
Can be installed on...						
Supporting floor (BCU)				•		•
Supporting wall (BCM, BCU)	•	•	•	•	•	•
Dimensions						
Reduced width			•	•	•	•
Reduced height	•	•				
Flush plate type						
Front	•		•	•		
Top		•				
Guarantee (years)	10	10	10	10	10	10
CE EN 14055 Class 2	•	•	•	•		

> Products highlights

> Wall hung WC flush plates:

A wide range of flush plates are available for wall hung WC's. As design is important, SIAMP offers different models to match with decorative trends. There is a wide choice of materials including ABS, aluminium alloy, stainless steel, or glass flush plates. Please see Flush plates' section on page 36 for more details.



• Robust and simple fixings

The BCM version, to be attached to a supporting wall, has 6 fixing points. The 2 at WC level transfer the weight directly to the supporting wall. The 2 at the top level and the 2 to the floor prevent the frame from wobbling.

The BCU version with its 6 fixations to a solid floor can steadily stand on its own without needing support from the wall.


• Corner solution

The optional set for installing BCM 350 & BCM 790 wall frames into corners allows 2 possibilities:

- typical 90° corner installation
- alongside wall installation up to a 30° angle from the wall itself



• Cistern



All our cisterns are shock resistant and highly resistant to thermal variations and ageing.

Our cisterns are insulated to reduce the risk of condensation and also help reduce noise.

All SIAMP products are leak tested before leaving the factory.



> Easy and safe installation:

• Steel structure

All of our metal frames are designed to pass the 400 kg and 250 kg load tests to meet the quality standard NF017. This is the only European test about the metal frame. Our frames also comply with EN 997 to ensure that the ceramic WC's resist a 400 kg load test themselves, not just the metal frame.



All our wall frames are treated with anti corrosion epoxy paint and then endurance tested with over 200 hours of salt spray.

> Equipment



Supplied complete with a dual flush outlet valve and a water saving and quiet fill inlet valve. These products are WRAS and NF approved and still undergo recurrent endurance tests (200 000 actuations).



For more information:
Web: siamp.co.uk

• Water saving

Our delayed action inlet valves help prevent additional fresh water being evacuated from the cistern before the flush is complete.

Please see Technical equipment's section on page 58 for more details.



• Flush efficiency

All our cisterns are designed to comply with EN 14055 Class 2 that requires the following performance:

- Leakage Proof
- Flow rates and flush volumes are constant
- Extended lifetime cycles
- Compatibility

They are designed to work with EN 997 Class 2 requirements for ceramic WC bowls, ensuring long term reliability and flush efficiency.



• Quiet fill

The integral design of our inlet valves helps reduce the water pressure that comes through the inlet. This reduced flow makes the inlet valve quieter than a traditional float valve. Please see Technical equipment's section on page 58 for more details.

• Secure supply

The water inlet connection can be made within the cistern to minimise the risk of any leakages. Our cisterns are supplied with an integral 1/2" brass isolating valve.



• Maintenance

Depending on the hardness of the water supply, it may be necessary to clean or change seals and membranes of the cistern equipment.

The flush plate serves as an access point and the cistern equipment is directly accessible and easy to take out of the tank.



> WALL FRAMES / WALL HUNG SOLUTIONS

Wall frames

Concealed cisterns

Flushing options

Wall hung accessories

Technical equipment

Toilet seats




> WALL HUNG SOLUTIONS

> WC frames:

- SIAMP offers a wide range of wall frames that can safely support wall hung WC's.
- The BCM 790 and the BCM 800 are designed to be installed with a low level flush plate. The BCM 790 features a front flush plate and the BCM 800 has a top flush plate.
- The BCM 350 and BCU 350 are both taller frames with a front flush plate.
- All of the frames must be attached to supporting walls except the BCU 350 which can be fixed to a solid floor.
- All of the cisterns comply with EN 14055 Class 2 and has integral WRAS approved fittings. This ensures compliance, reliability and flushing efficiency.
- An extensive range of flush plates are available for these wall frames.

> Washbasin and bidet frames:

- The BLM 400 allows support for a wall hung washbasin. When combined with a wall hung WC, it helps create modern bathroom styling.
- The SCU 350 supports either a wall hung bidet or can be used with a wall hung WC, in conjunction with a concealed cistern.



> Features

Wall frames		BCM 790	BCM 800	BCM 350	BCU 350	BLM 400	SCU 350
Fixing type	Supporting floor				•		•
	Supporting wall	•	•	•	•	•	•
Dimensions	Width (mm)	502	400	350	350*	400	350
	Height (mm)	790 ~ 990	800 ~ 1000	1100 ~ 1300	1100 ~ 1300	1100 ~ 1300	508 ~ 550
	Depth (mm)	150 ~ 245	180 ~ 245	142 ~ 245	Self-supporting 142**	80 ~ 245	140
					142 ~ 245		
	WC height fixing range (mm)	325 ~ 525	325 ~ 525	325 ~ 525	325 ~ 525	-	325 ~ 525
	WC fixing centers (mm)	180 / 230	180 / 230	180 / 230	180 / 230	-	180 / 230
Flush plate type	Front	Album 360, Album 90, Reflet 360, Reflet 90, Square, Segment, Smart, Smarty, Lemon, Ying Yang, Monovolume anti-vandals		Album 360, Album 90, Reflet 360, Reflet 90, Square, Segment, Smart, Smarty, Ying Yang, Lemon, Smart MVI, Monovolume anti-vandals		-	-
	Top		BCM 800			-	-
Miscellaneous	Can be adapted to less-able use	•	•	•	•	-	-
	Water saving and Delayed Action	•	•	•	•	-	-
	WC pack option			•		-	-
Guarantee (years)		10	10	10	10	10	10
 EN 14055		•	•	•	•	-	-



* Total width at the feet base: 385 mm

** For horizontal evacuation and 147 mm for vertical evacuation



For more information:
Web: siamp.co.uk

> Wall frame BCM 790



LOW HEIGHT
FRONT FLUSH PLATE

DESCRIPTION

- For installing a wall hung-standard, extended or compact WC
- Self-supporting wall frame for dry cladding bearing a 400kg load
- Designed for wall installation
- Low height wall frame solution for installation below windows, stairs etc.
- Steel tube structure, 30x30x1,5mm, electro-welded and anti-corrosion treated (epoxy paint withstanding 200 hours of salt spray), NF approved
- WC fixing using threaded rods (no need to cut them) and with possible adjustment after cladding completion
- Feet are made from epoxy painted steel plate (80x30x5mm) and electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor
- Can be fixed to the wall using 2 fixing brackets
- 6 litre cistern insulated against condensation, from which components can be accessed through the flush plate window. Conforms to WRAS, EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- Dual flush outlet valve, 6/4 litres factory preset, adjustable to 4/2.6 litres on site, WRAS approved
- Water saving and quiet fill delayed action inlet valve
- Choice of mechanical dual flush or anti-vandal single flush front flush plates

Connections:

- Water inlet connection on the inside of the cistern with 1/2" brass isolating valve
- Supplied with 90° outlet bend, which can be easily fixed on the frame by simply clipping it
- Supplied with accessories for protection during the construction phase

TEXT FOR TENDERS:

BCM 790

Ref.: 31 2790 10

Wall frame for wall hung WC, WRAS and NF approved components, 10-year guarantee, 6 supporting wall fixing points and 2 floor fixing points. Adjustable height from 790 to 990 mm, width 502 mm, adjustable depth from 150 to 245 mm. Factory preset flush at 6/4 litres, insulated cistern equipped with a dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Front flush plate actuation.



Supplied with 90° outlet bend made from PVC and WC connector.

Supplied without flush plate.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
BCM 790	31 2790 10	3 24723 009132 4	Carton	1	0,062	19,44	24

SUPPLEMENTS

Flush platesp. 36



- 1 = 150 ~ 245 mm
- 2 = 16 ~ 100 mm
- 4 = 0 ~ 185 mm
- if 3 = 400 => 4 = 185 mm max*
- if 3 = 480 => 4 = 105 mm max*

*When the distance between the WC fixing axle and the WC seat is 75 mm.

SIAMP


> Wall frame
BCM 800

**DESCRIPTION**

- For installing a wall hung-standard, extended or compact WC
- Self-supporting wall frame for dry cladding bearing a 400kg load, NF approved
- Designed for wall installation
- Low height wall frame solution for installation below windows, stairs etc.
- Steel tube structure, 30x30x1.5mm, electro-welded and anti-corrosion treated, (epoxy paint withstanding 200 hours of salt spray), NF approved
- WC fixing using threaded rods (no need to cut them) and with possible adjustment after cladding completion
- Feet are made from epoxy painted steel plate (100x30x8mm) and electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor
- Can be fixed to the wall using 2 fixing brackets
- 8,5 litre cistern insulated against condensation, from which components can be accessed through the flush plate window. Conforms to NF, EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- Dual flush outlet valve, 6/4 litres factory preset, adjustable to 4/2.6 litres on site, NF approved
- Water saving and quiet fill delayed action inlet valve, NF approved
- Mechanical dual flush with top flush plate BCM 800 bright chrome

Connections:

- Water inlet connection on the inside of the cistern with 1/2" brass isolating valve
- Supplied with 90° outlet bend, which can be easily fixed on the frame by simply clipping it
- Supplied with accessories for protection during the construction phase



TEXT FOR TENDERS:

BCM 800

Ref.: 31 1167 10


Wall frame for wall hung WC, NF approved components, 10-year guarantee, 6 supporting wall fixing points and 2 floor fixing points. Adjustable height from 800 to 1000 mm, width 400 mm, adjustable depth from 180 to 245 mm. Factory preset flush at 6/4 litres, insulated cistern equipped with a dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Top flush plate actuation.

Supplied with dual flush plate, 90° outlet bend made from PVC and WC connector.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
BCM 800	31 1167 10	3 24723 002371 4	Carton	1	0,077	13,35	24



For more information:
Web: siamp.co.uk



- 1** = 180 ~ 245 mm
2 = 20 ~ 100 mm
3 = 25 ~ 60 mm
5 = 0 ~ 200 mm
if 4 = 400 => 5 = 200 mm*
if 4 = 480 => 5 = 120 mm*

*When the distance between the WC fixing axle and the WC seat is 75 mm.

> Wall frame BCM 350



**NARROW
FRONT FLUSH PLATE**




DESCRIPTION

- For installing a wall hung-standard, extended or compact WC
- Self-supporting wall frame for dry cladding bearing a 400kg load, NF approved
- Designed for wall installation
- Steel tube structure, 30x30x1,5mm, electro-welded and anti-corrosion treated (epoxy paint withstanding 200 hours of salt spray), NF approved
- WC fixing using threaded rods (no need to cut them) and with possible adjustment after cladding completion
- Feet are made from epoxy painted steel plate (100x30x8mm) and electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor
- Can be fixed to the wall using 2 fixing brackets
- 6 litre cistern insulated against condensation, from which components can be maintained through the flush plate window. Conforms to NF, EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- Dual flush outlet valve, 6/4 litres factory preset, adjustable to 4/2.6 litres on site, NF approved
- Water saving and quiet fill delayed action inlet valve, NF approved
- Choice of mechanical dual flush, infra-red or anti-vandal single flush front flush plates

Connections:

- Water inlet connection on the inside of the cistern with 1/2" brass isolating valve
- Supplied with 90° outlet bend, which can be easily fixed on the frame by simply clipping it
- Supplied with accessories for protection during the construction phase



TEXT FOR TENDERS:

BCM 350


Ref.: 31 2315 13

Wall frame for wall hung WC, NF approved components, 10-year guarantee, 6 supporting wall fixing points and 2 floor fixing points. Adjustable height from 1100 to 1300 mm, width 350 mm, adjustable depth from 147 to 245 mm. Factory preset flush at 6/4 litres, insulated cistern equipped with a dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Front flush plate actuation. Supplied with 90° outlet bend made from PVC and WC connector. Supplied without flush plate.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
BCM 350	31 2315 13	3 24723 002022 5	Carton	1	0,07	15,82	28

SUPPLEMENTS

Flush platesp. 36



- 1 = 142/147~245 mm
- 2 = 16 ~ 100 mm
- 4 = 0 ~ 200 mm
- if 3 = 400 => 4 = 200 mm max*
- if 3 = 480 => 4 = 120 mm max*


*When the distance between the WC fixing axle and the WC seat is 75 mm.

SIAMP

> Wall frame BCU 350



**NARROW
FRONT FLUSH PLATE
FLOOR OR WALL INSTALLATION**




DESCRIPTION

- For installing a wall hung-standard, extended or compact WC
- Self-supporting wall frame for dry cladding bearing a 400kg load, NF approved
- Designed for floor or wall installation
- Steel tube structure, 45x45x1,5mm, electro-welded and anti-corrosion treated (epoxy paint withstanding 200 hours of salt spray), NF approved
- WC fixing using threaded rods (no need to cut them) and with possible adjustment after cladding completion
- Feet are made from epoxy painted steel plate (140x80x8mm) and electro-welded epoxy painted steel tubes (40x40x4mm), fixed to the floor
- Can be fixed to the wall using 2 fixing brackets
- 6 litre cistern insulated against condensation, from which components can be accessed through the flush plate window. Conforms to NF, EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- Dual flush outlet valve, 6/4 litres factory preset, adjustable to 4/2.6 litres on site, NF approved
- Water saving and quiet fill delayed action inlet valve, NF approved
- Choice of mechanical dual flush, infra-red or anti-vandal single flush front flush plates

Connections:

- Water inlet connection on the inside of the cistern with 1/2" brass isolating valve
- Supplied with 90° outlet bend, which can be easily fixed on the frame by simply clipping it
- Supplied with accessories for protection during the construction phase



TEXT FOR TENDERS:

BCU 350

Ref.: 31 2104 10

Wall frame for wall hung WC, NF approved components, 10-year guarantee, self supporting, possible wall fixing. Adjustable height from 1100 to 1300 mm, width 350 mm, adjustable depth from 147 to 245 mm. Factory preset flush at 6/4 litres, insulated cistern equipped with a dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Front flush plate actuation.


Supplied with 90° outlet bend made from PVC and WC connector.

Supplied without flush plate.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
BCU 350	31 2104 10	3 24723 009408 0	Carton	1	0,07	21,24	28

SUPPLEMENTS

Flush platesp. 36



1 = 147~245 mm
2 = 16/20** ~ 100 mm
4 = 0 ~ 200 mm
if 3 = 400 => 4 = 200 mm max*
if 3 = 480 => 4 = 120 mm max*

*When the distance between the WC fixing axle and the WC seat is 75 mm

**According to flush plate



For more information:
Web: siamp.co.uk

> Washbasin wall frame BLM 400



DESCRIPTION

- For installing a wall hung washbasin
- Wall frame bearing a 150kg load
- Designed for wall installation
- Steel tube structure, 30x30x1,5mm, electro-welded and anticorrosion treated (epoxy paint withstanding 200 hours of salt spray)
- Feet are made from epoxy painted steel plate (100x30x8mm) and electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor
- Can be fixed to the wall using 2 fixing brackets
- 2 water supply connection points
- Washbasin height adjustment
- Washbasin fixing accessories
- Water supply and drain height adjustable position
- Water inlet connection thanks to end-fittings 3/8" M/F
- Suitable for 32mm diameter PVC drain pipe


TEXT FOR TENDERS:

BLM 400


Ref.: 31 1250 10

Wall frame for wall hung washbasin, 10-year guarantee, 2 wall fixing points. Adjustable height from 1100 to 1300 mm, width 400 mm, adjustable depth from 80 to 245 mm. Adjustable height position of washbasin, water supply and drain.

Supplied with fixing and connection accessories.




- 1 = 80 ~ 245 mm
- 2 = 16 ~ 100 mm
- 3 = 0 ~ 200 mm
- 4 = 1100 ~ 1300 mm




	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
BLM 400	31 1250 10	3 24723 001346 3	Carton	1	0,025	10	40

> Bidet wall frame SCU 350



DESCRIPTION

- For installing a wall hung-standard or extended bidet
- Self supporting wall frame bearing a 400kg load
- Designed for floor or wall installation
- Steel tube structure, 45x45x1,5mm, electro-welded and anticorrosion treated, (epoxy paint withstanding 200 hours of salt spray)
- Bidet fixing using threaded rods
- Feet are made from epoxy painted steel plate (140x80x8mm) and electro-welded epoxy painted steel tubes (40x40x4mm), fixed to the floor
- Accepts bidet supply bent pipes from Ø 30 to 50mm
- Accepts bidet drain bent pipes from Ø 90 to 120mm
- Cistern or pressure bidet supply
- Supply bent pipe is maintained thanks to one clip collar
- Drainage pipe is maintained thanks to one clip collar
- Bidet drainage Ø38 ~ Ø45 mm fixation by one collar



TEXT FOR TENDERS:

SCU 350

Ref.: 31 2505 10

Wall frame for wall hung bidet, 10-year guarantee, self supporting, 4 floor fixing points. Adjustable height from 508 to 550 mm, width 350 mm. Bidet supply bent pipes from Ø 30 to 50 mm, bidet drain bent pipes from Ø 90 to 120 mm.

Supplied with floor and bidet fixing accessories.

Supplied without cistern, bent pipe and bidet connector.



1 = 140 mm min

2 = Cladding thickness

$y = 400 - 80 - x$ mm or $x =$ thickness of the ceramics at the bidet fixation level.
This calculation does not take into account any constraints due to the tank or pressurised water supply.

4 = 0 ~ 200 mm

if 3 = 400 => 4 = 200 mm max*

if 3 = 480 => 4 = 120 mm max*

*When the distance between the bidet fixing axle and the bidet seat is 75 mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
SCU 350	31 2505 10	3 24723 004670 6	Carton	1	0,02	11,45	60

> WALL FRAMES / WC PACKS

Wall frames

Concealed cisterns

Flushing options

Wall hung accessories

Technical equipment


Toilet seats



> WC PACKS

The SIAMP WC packs allow a single reference in a one box solution, comprising of a complete unit which includes a wall frame with cistern, flush plate, WC and seat.

SIAMP has two solutions, with the Deluxe version incorporating a water saving 4 litre flushing WC and a delayed action inlet valve.



> WC pack DELUXE SAMOA




COMPLETE PACK IN 1 BOX



DESCRIPTION

- BCM 350, wall fixing. Dual flush outlet valve, factory preset 4/2.6 litres flush, NF approved. Water saving and quiet fill delayed action inlet valve, NF approved. Conforms to EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations. See page 19 for more details
- Front flush plate operation. Supplied with bright chrome Smarty, dual flush plate, NF approved (see page 46 for more details), WC connector and drainage set
- White wall hung ceramic rimless hygienic WC Vitra S50. Conforms to EN 997 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- White thermoset Principauté Premium toilet seat, anti-bacterial, scratch resistant, soft close, with adjustable stainless steel hinges. See page 82 for more details

WATER SAVING:
DUAL FLUSH 4/2,6 LITRES



TEXT FOR TENDERS:

WC PACK DELUXE SAMOA

Ref.: 31 2338 10

Complete pack comprising BCM 350 wall frame, 6 litre insulated cistern with NF approved components. Factory preset at 4/2.6 litres with integral dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Front flush plate operation.

Supplied with fixing accessories for floor or wall fixing, dual flush plate, accessories for protection during the construction phase, ceramic rimless wall hung WC, thermoset anti-bacterial, soft close, white toilet seat, 90° outlet pipe and WC connectors.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
WC pack DELUXE SAMOA	31 2338 10	3 24723 009409 7	Carton	1	-	42,00	15




For more information:
Web: siamp.co.uk

> WC pack STANDARD SAMOA




COMPLETE PACK IN 1 BOX



DESCRIPTION

- BCM 350, wall fixing. Dual flush outlet valve, factory preset 6/4 litres flush, NF approved. Water saving and quiet fill delayed action inlet valve NF approved. Conforms to EN 14055 Class 2 flushing standards, BREEAM requirements and UK Building Regulations. See page 19 for more details
- Front flush plate operation. Supplied with bright chrome Ying Yang, dual flush plate, NF approved (see page 47 for more details), WC connector and drainage set
- White wall hung ceramic WC Vitra Normus. Conforms to NF, EN 997 Class 2 flushing standards, BREEAM requirements and UK Building Regulations
- White thermoplastic Opio Classic toilet seat, with stainless steel hinges, NF approved. See page 85 for more details



TEXT FOR TENDERS:

WC PACK STANDARD SAMOA

Ref.: 31 1858 15

Complete pack comprising BCM 350 wall frame, 6 litre insulated cistern with NF approved components. Factory preset at 6/4 litres with integral dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the inside of the cistern fitted with an integral isolating valve. Front flush plate operation.

Supplied with fixing accessories for floor or wall fixing, dual flush plate, accessories for protection during the construction phase, ceramic wall hung WC, white thermoplastic toilet seat with stainless steel hinges, 90° outlet pipe and WC connectors.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
WC pack STANDARD SAMOA	31 1858 15	3 24723 004059 9	Carton	1	0,131	38,00	15

> CONCEALED CISTERNS

Wall frames

Concealed cisterns

Flushing options

Wall hung accessories

Technical equipment

Toilet seats

> CONCEALED CISTERNS

> 3 water saving features*:

- A delayed action inlet valve prevents water loss when flushing. This product feature is available on several models.
- Cisterns are factory preset for delivering a water saving flush of 6 and 4 litres in compliance with EN 14055 Class 2.
- A reduced flush can easily be set at the time of installation on some models.

These 3 features are in line with BREEAM and other similar initiatives.

> Reliable:

- Cisterns are fully compliant with EN 14055 Class 2.
- The inlet & outlet valves installed in all our cisterns are WRAS approved.
- All SIAMP products go through lifetime endurance testing.

> Installation:

Into furniture:

- Intra is ideal for most furniture installations thanks to its compact dimensions, its front or top access and the versatility of its push button position.
- The Trueflow is the economical solution for standard bathroom furniture applications.

Behind cladding (plaster board, wood panel, etc.):


- The Intraslim B is the product for this type of installation as the flush plate access panel will allow for easy servicing.

All of the concealed cisterns can be reversed 180° for installation in dry risers in commercial buildings for ease of access and servicing.


> Flushing controls:

- Intra and Trueflow are operated by a cable push button.
- A version of the Intra can be fitted with a pneumatic push button.
- The Intraslim B is used in conjunction with a flush plate. A large variety of plates are available. See page 36 for more details.

* Depending on the model




> Features

Cisterns		INTRASLIM B	INTRA CABLE ECO	INTRA CABLE Bottom inlet	INTRA CABLE Side inlet	INTRA PN ECO	INTRA PN	TRUEFLOW
Installation	Recessed	•	•	•	•	•	•	•
	Low level	•	•	•	•	•	•	•
Inner equipment	Dual flush outlet valve	•	•	•	•	•	•	•
	Pneumatic outlet valve					•	•	
	Water saving and delayed action		•			•		
	Quiet fill inlet valve	•	•	•	•	•	•	•
	Brass tail	•	•		•	•		
Supply direction	Side	•			•			
	Bottom		•	•		•	•	•
Miscellaneous	Insulated cistern	•	•	•	•	•	•	•
	Complete delivery		•	•	•	•	•	•
Dimensions	Width (mm.)	510	460	460	460	460	460	436
	Height (mm.)	457	340	340	340	340	340	260
	Depth (mm.)	90	127	127	127	127	127	160
	Wall fixing centers	537 - 557						
Guarantee (years)		10	10	10	10	10	10	10
 EN 14055		•	•	•	•	•	•	•





> Concealed cistern INTRASLIM B



DESCRIPTION

- For wall hung or back to wall WC
- Recessed dry wall installation
- Low level installation
- Fixed on supporting wall
- Choice of mechanical dual flush front flush plates
- Cistern made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush outlet valve, 6/4l. factory preset, adjustable at 4,5/3l. on site
- Quiet fill inlet valve. WRAS and NF approved
- Water inlet connection on the inside of the cistern with 1/2" brass isolating valve
- Supply pipe with reversible fixing bracket
- Supply sleeve with pan seal



TEXT FOR TENDERS:

INTRASLIM B

Ref.: 31 9032 10

Concealed cistern for wall hung or back to wall WC. WRAS and NF approved components, 10-year guarantee. Dual flush front flush plate. 6 litres insulated cistern equipped with a dual flush outlet valve and a quiet fill inlet valve. Water inlet connection on the inside of the cistern with 1/2" brass tail. Supply pipe with reversible fixing bracket. Dimensions height 457 mm, width 510 mm and depth 90 mm.

Delivered with fixing and connection accessories.


Supplied without flush plate and drain accessories.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRASLIM B	31 9032 10	3 24723 005275 2	Carton	1	0,043	2,84	42

SUPPLEMENTS


Flush platesp. 36

> Concealed cistern INTRA CABLE ECO Bottom inlet



DESCRIPTION

- For back to wall WC
- Recessed with an access cover inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote cable flushing
- Bright chrome dual flush top or front flushing
- Cistern and lid made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush cable outlet valve, 6/4l. factory preset, adjustable at 4/2,6l. on site. WRAS and NF approved
- Water saving and quiet fill delayed action inlet valve
- Bottom inlet supply
- 1/2" brass water inlet connection
- Height and depth adjustable supply pipe with pan seal
- Can be adapted for less able use



TEXT FOR TENDERS:

INTRA CABLE ECO Bottom inlet Ref.: 31 0150 10

Concealed cistern for floor mounted, back to wall WC. WRAS and NF approved components, 10-year guarantee. Cable flushing, bright chrome dual flush top or front flushing. 6 litres insulated cistern equipped with a dual flush outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the bottom of the cistern with 1/2" brass tail. Dimensions height 340 mm, width 460 mm and depth 127 mm. Complete delivery with fixing and connection accessories.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRA CABLE ECO Bottom inlet	31 0150 10	3 24723 009406 6	Carton	1	0,029	2,82	84


OPTIONS

Flushingp. 36




For more information:
Web: siamp.co.uk

> Concealed cistern INTRA CABLE Bottom inlet



DESCRIPTION

- For back to wall WC
- Recessed with an access cover inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote cable flushing
- Bright chrome dual flush top or front flushing
- Cistern and lid made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush cable outlet valve, 6/4l. factory preset. WRAS and NF approved
- Quiet fill inlet valve
- Bottom inlet supply
- 1/2" plastic water inlet connection
- Height and depth adjustable supply pipe with pan seal
- Can be adapted for less able use



TEXT FOR TENDERS:

INTRA CABLE Bottom inlet

Ref.: 31 0147 10

Concealed cistern for floor mounted, back to wall WC. WRAS and NF approved components, 10-year guarantee. Cable flushing, bright chrome dual flush top or front flushing. 6 litres insulated cistern equipped with a dual flush outlet valve and a quiet fill inlet valve. Water inlet connection on the bottom of the cistern with 1/2" plastic tail. Dimensions height 340 mm, width 460 mm and depth 127 mm.

Complete delivery with fixing and connection accessories.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRA CABLE Bottom inlet	31 0147 10	3 24723 002372 1	Carton	1	0,029	2,82	84

OPTIONS


Flushingp. 36

> Concealed cistern INTRA CABLE Side inlet



DESCRIPTION

- For back to wall WC
- Recessed with an access cover inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote cable flushing
- Bright chrome dual flush top or front flushing
- Cistern and lid made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush cable outlet valve, 6/4l. factory preset. WRAS and NF approved
- Quiet fill inlet valve
- Side inlet supply on the right
- 1/2" brass water inlet connection
- Height and depth adjustable supply pipe with pan seal
- Can be adapted for less able use



TEXT FOR TENDERS:

INTRA CABLE Side inlet

Ref.: 31 0148 10

Concealed cistern for floor mounted, back to wall WC. WRAS and NF approved components, 10-year guarantee. Cable flushing, bright chrome dual flush top or front flushing. 6 litres insulated cistern equipped with a dual flush outlet valve and a quiet fill inlet valve. Water inlet connection on the right side of the cistern with 1/2" brass tail. Dimensions height 340 mm, width 460 mm and depth 127 mm.

Complete delivery with fixing and connection accessories.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRA CABLE Side inlet	31 0148 10	3 24723 002194 9	Carton	1	0,029	2,82	84


OPTIONS

Flushingp. 36



For more information:
Web: siamp.co.uk

> Concealed cistern INTRA PNEUMATIC ECO Bottom inlet



DESCRIPTION

- For back to wall WC
- Recessed with an access cover inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote pneumatic flushing
- Bright chrome dual flush flushing
- 2m air hose with corrugated pipe protection
- Cistern and lid made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush pneumatic outlet valve, 6/4l. factory preset, adjustable at 5/3l. on site. WRAS and NF approved
- Water saving and quiet fill delayed action inlet valve
- Bottom inlet supply
- 1/2" brass water inlet connection
- Height and depth adjustable supply pipe with pan seal
- Can be adapted for less able use


TEXT FOR TENDERS:

INTRA PNEUMATIC ECO Bottom inlet

Ref.: 31 0154 10

Concealed cistern for floor mounted, back to wall WC. WRAS and NF approved components, 10-year guarantee. Remote pneumatic flushing, bright chrome dual flush flushing. 6 litres insulated cistern equipped with a dual flush pneumatic outlet valve and a water saving and quiet fill delayed action inlet valve. Water inlet connection on the bottom of the cistern with 1/2" brass tail. Dimensions height 340 mm, width 460 mm and depth 127 mm.

Complete delivery with fixing and connection accessories, flushing, air hose with corrugated pipe protection.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRA PNEUMATIC ECO Bottom inlet	31 0154 10	3 24723 009407 3	Carton	1	0,029	2,82	84

OPTIONS

Flushingp. 36

> Concealed cistern INTRA PNEUMATIC Bottom inlet



DESCRIPTION

- For back to wall WC
- Recessed with an access cover inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote pneumatic flushing
- Bright chrome dual flush flushing
- 2m air hose with corrugated pipe protection
- Cistern and lid made from HDPE
- 6 litres insulated cistern. Conforms to EN 14055 class 2 flushing standards
- Outer anti-condensation PSE insulation
- Dual flush pneumatic outlet valve, 6/4l. factory preset. WRAS and NF approved
- Quiet fill inlet valve
- Bottom inlet supply
- 1/2" plastic water inlet connection
- Height and depth adjustable supply pipe with pan seal
- Can be adapted for less able use


TEXT FOR TENDERS:

INTRA PNEUMATIC Bottom inlet

Ref.: 31 0144 11

Concealed cistern for floor mounted, back to wall WC. WRAS and NF approved components, 10-year guarantee. Remote pneumatic flushing, bright chrome dual flush flushing. 6 litres insulated cistern equipped with a dual flush pneumatic outlet valve and a quiet fill inlet valve. Water inlet connection on the bottom of the cistern with 1/2" plastic tail. Dimensions height 340 mm, width 460 mm and depth 127 mm.

Complete delivery with fixing and connection accessories, flushing, air hose with corrugated pipe protection.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
INTRA PNEUMATIC Bottom inlet	31 0144 11	3 24723 003482 6	Carton	1	0,029	2,82	84

OPTIONS

Flushingp. 36





For more information:
Web: siamp.co.uk

> Concealed cistern TRUEFLOW



DESCRIPTION

- For back to wall WC
- For use inside wall or furniture
- Low level installation
- Wall or furniture fixing
- Remote cable flushing
- Bright chrome dual flush top or front flushing
- Cistern and lid made from PS
- 6 litres cistern. Conforms to EN 14055 class 2 flushing standards
- Dual flush cable outlet valve, 6/4l. factory preset. WRAS and NF approved
- Quiet fill inlet valve
- Bottom inlet supply
- 1/2" plastic water inlet connection
- Height and depth adjustable supply pipe with pan seal



TEXT FOR TENDERS:

TRUEFLOW

Ref.: 31 0144 11

Concealed cistern for back to wall WC. WRAS and NF approved components. Cable flushing, bright chrome dual flush top flushing. 6 litres cistern equipped with a dual flush outlet valve and a quiet fill inlet valve. Water inlet connection on the bottom of the cistern with 1/2" plastic tail. Dimensions height 436 mm, width 260 mm and depth 160 mm. Delivered with fixing and connection accessories.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
TRUEFLOW Bottom inlet	31 0147 18	3 24723 002518 3	Carton	1	0,012	2,25	96

OPTIONS

Flushingp. 36

> FLUSHING OPTIONS

Wall frames


Concealed cisterns

Flushing options

Wall accessories

Technical equipment

Toilet seats



> FLUSHING OPTIONS


A wide range of flush plates and buttons are available for the wall frames and cisterns.

All our flush plates and buttons are designed to operate with minimal actuation effort.

Our automatic flush plate range SMART infra-red is hygienic and meets the requirements of inclusive design.

The pneumatic or cable flushing options allow comfortable positioning in relation to the cistern. They can also be fitted with a choice of buttons for people with reduced mobility.

The range of flush plates are made with various materials including ABS, metal, glass or laminate. Classic or modern, resistant and practical, these materials and the varied designs allows you to choose the most suitable option based upon application or aesthetics.



> Features

Flushing options / Wall frames & cisterns

Flushing options / Wall frames & Cisterns	BCM 790	BCM - BCU 350	Intra	Intraslim B
Album 360 & 90	•	•		•
Reflet 360 & 90	•	•		•
Square	•	•		•
Segment	•	•		•
Smart	•	•		•
Smarty	•	•		•
Ying Yang	•	•		•
Lemon	•	•		•
Monovolume anti-vandal	•	•		•
Smart infra-red		•		
Pneumatic anti-vandal			•	
Pneumatic button (flush fitting)			•	
Pneumatic button (raised)			•	
Extended cable flushing			•	
Less able raised button			•	

Flushing specifications

Specifications / Flushing options	Flush volume		Flush type				Position		Material				Less able	Guarantee (years)	NF
	Single	Dual	Mechanical	Pneumatic	Automatic	Cable	Front	Remote	ABS	Metal	Glass	Wood panel			
Album 360 & 90		•	•				•		•			•		2	•
Reflet 360 & 90		•	•				•		•		•			2	•
Square		•	•				•		•					2	•
Segment		•	•				•		•					2	•
Smart		•	•				•			•				2	•
Smarty		•	•				•		•					2	•
Ying Yang		•	•				•		•					2	•
Lemon		•	•				•		•					2	•
Monovolume anti-vandal	•		•				•		•	•				2	
Smart infra-red	•				•		•			•			•	2	
Pneumatic anti-vandal	•			•				•	•					2	•
Pneumatic button (flush fitting)		•		•				•	•					2	•
Pneumatic button (raised)	•			•				•	•				•	2	•
Extended cable flushing		•				•		•	•					2	
Less able raised button	•					•		•	•				•	2	



For more information:
Web: siamp.co.uk

> ALBUM 360

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B





Natural Oak & Bright chrome buttons



DESCRIPTION

- Modern and round design
- Decorative wood panel made from high pressure laminated compact boards
- Resistant plate to shocks and moisture
- Decorated ABS buttons and surrounding frame
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 20 and 100 mm



Stone Grey & Bright chrome buttons



Black & Bright chrome buttons

TEXT FOR TENDERS:

ALBUM 360

Ref.: 31 17..... 10

Dual flush actuation plate, made from wood panel, finish and bright chrome plated surrounding frame and round design buttons. 2-year guarantee. Resistant to shocks and moisture. Dimensions height 180 mm, width 236 mm and depth 13 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
ALBUM 360 Natural Oak / Bright chrome	31 1790 10	3 24723 005126 7	Carton	10	0,072	12	-
ALBUM 360 Stone Grey / Bright chrome	31 1791 10	3 24723 005128 1	Carton	10	0,072	12	-
ALBUM 360 Black / Bright chrome	31 1792 10	3 24723 005130 4	Carton	10	0,072	12	-

> ALBUM 90

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B





Natural Oak & Bright chrome buttons



DESCRIPTION

- Modern and angular design
- Decorative wood panel made from high pressure laminated compact boards
- Resistant plate to shocks and moisture
- Decorated ABS buttons and surrounding frame
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 20 and 100 mm



Stone Grey & Bright chrome buttons

TEXT FOR TENDERS:

ALBUM 90

Ref.: 31 16..... 10

Dual flush actuation plate, made from wood panel, finish and bright chrome plated surrounding frame and angular design buttons. 2-year guarantee. Resistant to shocks and moisture. Dimensions height 180 mm, width 236 mm and depth 13 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
ALBUM 90 Natural Oak / Bright chrome	31 1690 10	3 24723 005134 2	Carton	10	0,072	12	-
ALBUM 90 Stone Grey / Bright chrome	31 1691 10	3 24723 005135 9	Carton	10	0,072	12	-
ALBUM 90 Black / Bright chrome	31 1692 10	3 24723 005136 6	Carton	10	0,072	12	-




Black & Bright chrome buttons



For more information:
Web: siamp.co.uk

> REFLET 360

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B





White glass & Matt chrome buttons




DESCRIPTION

- Modern and round design
- Decorated glass plate with light and depth effects
- Toughened glass
- Decorated ABS buttons and frame
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 20 and 100 mm



Black glass & Matt chrome buttons



Natural green glass & Matt chrome buttons

TEXT FOR TENDERS:

REFLET 360

Ref.: 31 19..... 10


Dual flush actuation plate, made from toughened glass, finish and matt chrome plated finish round design buttons. 2-year guarantee. Dimensions height 180 mm, width 236 mm and depth 13 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
REFLET 360 White / Matt chrome	31 1984 10	3 24723 004210 4	Carton	10	0,072	12	-
REFLET 360 Black / Matt chrome	31 1981 10	3 24723 002359 2	Carton	10	0,072	12	-
REFLET 360 Natural green / Matt chrome	31 1982 10	3 24723 002358 5	Carton	10	0,072	12	-

> REFLET 90

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B




White glass & Matt chrome buttons



DESCRIPTION

- Modern and angular design
- Decorated glass plate with light and depth effects
- Toughened glass
- Decorated ABS buttons and frame
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 20 and 100 mm



Black glass & Matt chrome buttons

TEXT FOR TENDERS:


REFLET 90

Ref.: 31 19..... 10

Dual flush actuation plate, made from toughened glass, finish and matt chrome plated finish angular design buttons. 2-year guarantee. Dimensions height 180 mm, width 236 mm and depth 13 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
REFLET 90 White / Matt chrome	31 1934 10	3 24723 004212 8	Carton	10	0,072	12	-
REFLET 90 Black / Matt chrome	31 1931 10	3 24723 002285 4	Carton	10	0,072	12	-
REFLET 90 Natural green / Matt chrome	31 1932 10	3 24723 002286 1	Carton	10	0,072	12	-




Natural green glass & Matt chrome buttons



For more information:
Web: siamp.co.uk

> SQUARE




Can be installed on BCM 790, BCM - BCU 350 and Intraslim B




Black & Bright chrome inserts

DESCRIPTION


- Modern and angular design
- Made from ABS
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 16 and 100 mm



White & Bright chrome inserts



Stainless steel finish & Bright chrome inserts



Bright chrome & Matt chrome inserts

TEXT FOR TENDERS:

SQUARE

Ref.: 31 20.... 10


Dual flush actuation plate, finish rectangular plate and square buttons, square inserts. 2-year guarantee. Dimensions height 176 mm, width 200 mm and depth 8,5 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
SQUARE White / Bright chrome inserts	31 2040 10	3 24723 002425 4	Carton	40	0,096	16,4	-
SQUARE Black / Bright chrome inserts	31 2041 10	3 24723 002426 1	Carton	40	0,096	16,4	-
SQUARE Stainless steel finish / Bright chrome inserts	31 2042 10	3 24723 002427 8	Carton	40	0,096	16,4	-
SQUARE Bright chrome / Matt chrome inserts	31 2072 10	3 24723 002430 8	Carton	40	0,096	16,4	-

> SEGMENT

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B




White & Bright chrome inserts



DESCRIPTION


- Modern design underlined by chrome inserts
- Made from ABS
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 16 and 100 mm



Black & Bright chrome inserts



Stainless steel finish & Bright chrome inserts



Bright chrome & Matt chrome inserts

TEXT FOR TENDERS:

SEGMENT

Ref.: 31 17.... 10

Dual flush actuation plate, finish rectangular plate and buttons, inserts. 2-year guarantee. Dimensions height 176 mm, width 200 mm and depth 8,5 mm.

Delivered with back fixing frame, 2 fixing screws and 2 actuation screws.


	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
SEGMENT White / Bright chrome inserts	31 1710 10	3 24723 002417 9	Carton	40	0,096	16	-
SEGMENT Black / Bright chrome inserts	31 1711 10	3 24723 002418 6	Carton	40	0,096	16	-
SEGMENT Stainless steel finish / Bright chrome inserts	31 1712 10	3 24723 002419 3	Carton	40	0,096	16	-
SEGMENT Bright chrome / Matt chrome inserts	31 1722 10	3 24723 002422 3	Carton	40	0,096	16	-



For more information:
Web: siamp.co.uk

> SMART

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B




Bright chrome





DESCRIPTION

- Modern design
- Made from aluminium alloy
- Decorative versions : bright chrome plated and matt chrome finish
- Vandal resistant
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 16 and 100 mm



Matt chrome



TEXT FOR TENDERS:

SMART

Ref.: 31 18... 10

Dual flush actuation plate, made from aluminium alloy, finish, including a vandal resistant system. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 11 mm.

Delivered with wall fixing frame, 2 fixing screws, 2 actuation screws and 1 vandal resistant headless screw M4x12. Necessary spanner.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
SMART Bright chrome & Vandal resistant	31 1874 10	3 24723 001958 8	Carton	16	0,094	12,8	-
SMART Matt chrome & Vandal resistant / Fingerprints proof	31 1872 10	3 24723 002073 7	Carton	16	0,094	12,8	-


> SMARTY

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B




DESCRIPTION


- Modern design
- Made from ABS
- Decorative versions:
 - White
 - Bright chrome (bright chrome plated plate and large button, matt chrome finish for small button)
 - Matt chrome (matt chrome finish for plate and large button, bright chrome plated small button)
- Dual flush
- Mechanical actuation
- Actuation force below 20 Newton
- Smooth actuating screws to avoid operating noise
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Flush plate serves as an access point for reaching the cistern equipment
- Cladding thickness between 16 and 100 mm





White



Bright chrome



Matt chrome



TEXT FOR TENDERS:

SMARTY

Ref.: 31 19... 10

Dual flush actuation plate, made from ABS, finish. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 11 mm.

Delivered with wall fixing frame, 2 fixing screws and 2 actuation screws.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
SMARTY White	31 1910 10	3 24723 002087 4	Carton	40	0,096	15,6	-
SMARTY Bright chrome	31 1912 10	3 24723 002090 4	Carton	40	0,096	15,6	-
SMARTY Matt chrome	31 1911 10	3 24723 002088 1	Carton	40	0,096	15,6	-



For more information:
Web: siamp.co.uk

> YIN YANG

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B



DESCRIPTION

- > Zen design
- > Made from ABS
- > Decorative versions :
 - White
 - Bright chrome plated
 - Bright chrome (bright chrome plated frame and large button and matt chrome finish for small button)
 - Matt chrome (matt chrome finish for plate and large button, bright chrome plated small button)
- > Dual flush
- > Mechanical actuation
- > Actuation force below 20 Newton
- > Smooth actuating screws to avoid operating noise
- > Hand cuttable fixing and actuation screws for adapting length to cladding
- > Flush plate serves as an access point for reaching the cistern equipment
- > Cladding thickness between 16 and 100 mm



White




Bright chrome



Bright chrome & Matt chrome



Matt chrome & Bright chrome



TEXT FOR TENDERS:

YIN YANG

Ref.: 31 18... 10


Dual flush actuation plate, made from ABS, finish. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 22 mm.

Delivered with wall fixing frame, 2 fixing screws and 2 actuation screws. Necessary spanner.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
YIN YANG White	31 1800 10	3 24723 001304 3	Carton	40	0,096	14	-
YIN YANG Bright chrome	31 1853 16	3 24723 001899 4	Carton	40	0,096	14	-
YIN YANG Bright chrome / Matt chrome	31 1853 10	3 24723 001489 7	Carton	40	0,096	14	-
YIN YANG Matt chrome / Bright chrome	31 1850 10	3 24723 001305 0	Carton	40	0,096	14	-

> LEMON

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B





Bright chrome

DESCRIPTION

- > Lemon design
- > Made from ABS
- > Decorative versions:
 - Bright chrome (bright chrome plated frame and large button and matt chrome finish for small button)
 - Matt chrome (matt chrome finish for plate and large button, bright chrome plated small button)
- > Dual flush
- > Mechanical actuation
- > Actuation force below 20 Newton
- > Flush plate serves as an access point for reaching the cistern equipment
- > Smooth actuating screws to avoid operating noise
- > Hand cuttable fixing and actuation screws for adapting length to cladding
- > Flush plate serves as an access point for reaching the cistern equipment
- > Cladding thickness between 16 and 100 mm



Matt chrome



TEXT FOR TENDERS:

LEMON

Ref.: 31 18... 10

Dual flush actuation plate, made from ABS, finish. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 18 mm.

Delivered with wall fixing frame, 2 fixing screws and 2 actuation screws. Necessary spanner.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
LEMON Bright chrome	31 1814 10	3 24723 001680 8	Carton	40	0,096	15,6	-
LEMON Matt chrome	31 1813 10	3 24723 001679 2	Carton	40	0,096	15,6	-



For more information:
Web: siamp.co.uk



> MONOVOLUME ANTI-VANDAL

Can be installed on BCM 790, BCM - BCU 350 and Intraslim B



DESCRIPTION

- Remote flushing
- Made from stainless steel
- Vandal resistant
- Single flush
- Mechanical actuation
- Actuation force below 20 Newton
- Flush plate serves as an access point for reaching the cistern equipment
- Hand cuttable fixing and actuation screws for adapting length to cladding
- Cladding thickness between 16 and 100 mm



TEXT FOR TENDERS:

Monovolume anti-vandal single flush, stainless steel

Ref.: 31 1888 10



Single flush actuation plate, made from stainless steel, including a vandal resistant system. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 24 mm.

Delivered with wall fixing frame, 2 fixing screws, 2 actuation screws and 1 vandal resistant headless screw 12. Necessary spanner.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Monovolume anti-vandal single flush, stainless steel	31 1888 10	3 24723 001408 8	Carton	40	0,096	27,2	-



> SMART MV INFRA-RED

Can be installed on BCM - BCU 350



DESCRIPTION

- > Modern and smart design
- > Made from aluminium alloy
- > Matt chrome finish
- > Automatic pan flushing
- > User does not need to touch buttons, which prevents bacteria, mould and fungi transmission
- > Vandal resistant
- > Single flush
- > Automatic infra-red actuation:
 - senses user presence after 12 seconds
 - infra-red beam reaches a distance of 60 cm and has a 22° radius from sensor
 - flushes once user has left
 - servomotor flush valve actuation
 - very low voltage power supply (using transformer)
- > Failure function:
 - Flush can be performed with manual button
 - Actuation force below 20 Newton
- > Smooth actuating screws to avoid operating noise
- > Hand cuttable fixing and actuation screws for adapting length to cladding
- > Flush plate serves as an access point for reaching the cistern equipment
- > Cladding thickness between 16 and 100 mm



TEXT FOR TENDERS:


SMART MVI

Ref.: 31 19... 10

Single flush actuation plate, made from aluminium alloy matt chrome finish, including a automatic infra-red actuation with a servomotor flush valve actuation, supplied with a manual button flush and a vandal resistant system. 2-year guarantee. Dimensions height 180 mm, width 200 mm and depth 11 mm.

Delivered with wall fixing frame, 2 fixing screws, 1 actuation screw, 1 base supporting the servomotor, 1 cable transformer, 1 case flush IP54, 1 protective tube and 1 vandal resistant headless screw M4x12. Necessary spanner.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
SMART MVI Matt chrome	31 1950 10	3 24723 002148 2	Carton	12	0,14	18	-



For more information:
Web: siamp.co.uk



> SMART MV INFRA-RED BATTERY

Can be installed on BCM - BCU 350



DESCRIPTION

- > Modern and smart design
- > Made from aluminium alloy
- > Matt chrome finish
- > Automatic pan flushing
- > User does not need to touch buttons, which prevents bacteria, mould and fungi transmission
- > Vandal resistant
- > Single flush
- > Automatic infra-red actuation:
 - senses user presence after 12 seconds
 - infra-red beam reaches a distance of 60 cm and has a 22° radius from sensor
 - flushes once user has left
 - servomotor flush valve actuation
 - battery power supply (rechargeable or original)
- > Function failure:
 - Flush can be performed with manual button
 - Actuation force below 20 Newton
- > Smooth actuating screws to avoid operating noise
- > Hand cuttable fixing and actuation screws for adapting length to cladding
- > Flush plate serves as an access point for reaching the cistern equipment
- > Cladding thickness between 16 and 100 mm



TEXT FOR TENDERS:


SMART MVI BATTERY

Ref.: 31 1954 10

Single flush actuation plate, made from aluminium alloy, matt chrome finish, including a automatic infra-red actuation with a servomotor flush valve actuation, supplied with a manual button flush and a vandal resistant system. 2-year guarantee. Dimensions height 180mm, width 200 mm and depth 11 mm.

Delivered with wall fixing frame, 2 fixing screws, 1 actuation screw, 1 base supporting the servomotor, 1 battery-powered case and 1 vandal resistant headless screw M4x12. Necessary spanner.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
SMART MVI BATTERY Matt chrome	31 1954 10	3 24723 003452 9	Carton	12	0,14	18	-





> PNEUMATIC ANTI-VANDAL BUTTON

Can be installed on Intra PN



DESCRIPTION

- Remote flushing
- Stainless steel vandal resistant plate, fixing by Torx screws
- Button and its mechanism made from ABS
- Bright chrome plated button and stainless steel surround
- Single flush
- Flush fitting button
- Pneumatic actuation
- Pneumatic pipe of 2 m with protection sheath included within the cistern



TEXT FOR TENDERS:

Pneumatic anti-vandal single flush button, bright chrome and stainless steel

Ref.: 31 2552 10

Single flush, vandal resistant, with stainless steel frame and bright chrome plated ABS button, pneumatic actuation. 2-year guarantee. Dimensions height 140 mm and width 140 mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Pneumatic anti-vandal single flush button, bright chrome and stainless steel	31 2552 10	3 24723 003948 7	Carton	1	-	-	-




For more information:
Web: siamp.co.uk

> PNEUMATIC FLUSHING

Recessed with flush fitting button

Can be installed on Intra PN



DESCRIPTION

- Remote flushing
- Bright chrome plated finish
- Made from ABS
- Dual flush
- Flush fitting buttons
- Pneumatic actuation
- Pneumatic pipe of 2 m with protection sheath included within the cistern
- Ø 75 mm hole recessed installation
- Fixing accessories included

TEXT FOR TENDERS:

Pneumatic dual flush button, flush fitting, bright chrome

Ref.: 31 2551 10

Dual flush, with ABS flush fitting buttons, bright chrome plated finish, pneumatic actuation, Ø 75 mm hole recessed installation, Ø 120 mm plated rosette. 2-year guarantee.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Pneumatic dual flush button, flush fitting, bright chrome	31 2551 10	3 24723 003790 2	Carton	18	0,048	4,9	-

> PNEUMATIC FLUSHING

Recessed with raised less-able button

Can be installed on Intra PN



DESCRIPTION

- Remote flushing
- Decorative versions : white or bright chrome plated
- Made from ABS
- Single flush
- Raised button with external actuation range dedicated to less able people, seniors and juniors
- Pneumatic actuation
- Pneumatic pipe of 2 m with protection sheath included within the cistern
- Ø 75 mm hole recessed installation



TEXT FOR TENDERS:

Pneumatic single flush, recessed with raised button, white

Ref.: 31 2535 10

Single flush, with ABS raised button, white finish, pneumatic actuation, Ø 75 mm hole recessed installation, Ø 120 mm plated rosette. 2-year guarantee.

Pneumatic single flush, recessed with raised button, bright chrome

Ref.: 31 2555 10

Single flush, with ABS raised button, bright chrome plated finish, pneumatic actuation, Ø 75 mm hole recessed installation, Ø 120 mm plated rosette. 2-year guarantee.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Pneumatic single flush, recessed with raised button, white	31 2535 10	3 24723 002496 4	Carton	18	0,048	4,5	-
Pneumatic single flush, recessed with raised button, bright chrome	31 2555 10	3 24723 003791 9	Carton	18	0,048	4,5	-



For more information:
Web: siamp.co.uk



> Extended Cable Flushing

Can be installed on Intra cable and Trueflow



DESCRIPTION

- > Remote flushing
- > Wall crossing up to 150 mm.
- > Recessed installation
- > Push button made from ABS
- > Push button bright chrome plated finish
- > Dual flush
- > Cable actuation
- > Actuation force below 20 Newton
- > Wall crossing tube made from aluminium



> Optima series raised buttons



DESCRIPTION

- > Remote flushing
- > Bright chrome finish
- > Made from ABS
- > Single flush
- > Raised button with external actuation range dedicated to less able people, seniors and juniors
- > Cable actuation



TEXT FOR TENDERS:

Extended cable flushing dual flush 800/70

Ref.: 31 5005 10

Dual flush, made from ABS, bright chrome plated finish, Ø 55 mm hole recessed installation, outer casing made from aluminium, cable actuation, wall crossing up to 70 mm. 2-year guarantee.

Extended cable flushing dual flush 800/150


Ref.: 31 5004 10

Dual flush, made from ABS, bright chrome plated finish, Ø 55 mm hole recessed installation, outer casing made from aluminium, cable actuation, wall crossing up to 150 mm. 2-year guarantee.

Optima Raised buttons

Ref.: 34 07

Single flush, with ABS raised button, bright chrome finish, cable actuation, Ø 16 mm hole recessed installation, Ø 58 mm plated rosette. 2-year guarantee.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Extended cable flushing dual flush 800/70	31 5005 10	3 24723 002142 0	Carton	1	-	-	-
Extended cable flushing dual flush 800/150	31 5004 10	3 24723 002141 3	Carton	1	-	-	-
Optima S raised button	34 7051 07	3 24723 004273 9	Bag	250	0,07	12,5	-
Optima 49 raised button	34 5054 07	3 24723 004328 6	Bag	250	0,07	12,5	-
Optima 50 raised button	34 5051 07	3 24723 004274 6	Bag	250	0,07	12,5	-


> WALL HUNG ACCESSORIES

> CORNER FIXING BRACKETS

The optional set for installing BCM 790, 800 & 350 wall frames into corners allows 2 possibilities:

- typical 90° corner installation
- alongside wall installation up to a 30° angle from the wall itself

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
Corner fixing top brackets	34 1064 07	3 24723 009410 3	Bag	1	-	-	-
Corner fixing WC brackets	34 1065 07	3 24723 009411 0	Bag	1	-	-	-



> BENT DRAINAGE SET

- 90° bent pipe for connecting the frame to the building's drainage system: diameter 100 mm, made from PVC, to be glued, EPDM pan seal. Fixing the bent pipe on the frame by simply clipping it with the bracket attached to the frame
- Short straight connector for connecting WC to bent pipe: diameter 100 mm, made from PVC, EPDM pan seal

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
Bent drainage set	92 4000 07	3 24723 001277 0	Bag	1	-	-	-



> STRAIGHT DRAINAGE SET

- Long straight connector for connecting the frame to the building's drainage system: diameter 100mm, made from PVC, to be glued, EPDM pan seal. Fixing the pipe on the frame by simply clipping it with the bracket attached to the frame
- Short straight connector for connecting WC to the the long pipe: diameter 100mm, made from PVC, EPDM pan seal

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
Straight drainage set	92 4010 07	3 24723 001278 7	Bag	1	-	-	-




For more information:
Web: siamp.co.uk

> WALL HUNG ACCESSORIES

> 100-110MM ADAPTER R110

- Connector in between Ø 110 mm female and Ø 100 mm male pipe
- Made from PVC
- To be glued



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
100-110mm adapter R110	92 3060 52	3 24723 009431 8	Bulk	45	-	-	-

> LONG SUPPLY SLEEVE STRAIGHT CONNECTOR

- For use where there is an oversized recess or void between the frame and the outer wall
- Supply straight connector, length 450 mm



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Long supply sleeve straight connector	92 0145 07	3 24723 001961 8	Bag	1	-	-	-

> EXTENDED RODS

- For use where there is an oversized recess or void between the frame and the outer wall
- M12 male, M12 female
- Extension length : 78 mm



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Extended rods	34 1151 07	3 24723 001962 5	Bag	2	-	-	-

> EXTENDED FLUSH PLATE FIXING SCREWS

- For cladding ranging between 100 and 250 mm
- Length: 250 mm



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
Extended flush plate fixing screws	34 1149 46	3 24723 009436 3	Bag	4	-	-	-

> TECHNICAL EQUIPMENT

Wall frames

Concealed cisterns

Flushing options

Wall hung accessories

Technical equipment

Toilet seats




> Inlet Valves & Flush Valves

Chosen by many global bathroom brands to equip their cisterns, the SIAMP range of inlet valves and flush valves offers quality and durability, guaranteed by WRAS, NF and many other international standards.

Made with premium and recyclable raw materials, our products are continually tested and certified with manufacturing and product sustainability in mind, meaning SIAMP can offer a guarantee of 10 years across the range.



Expectations of comfort (quiet, ease of operation, simple to install) and water saving has led to the development of concepts covered by numerous international patents.



> Product features

UNIVERSAL
BAYONNET

- > Matches any SIAMP flush valves
- > Easily exchangeable with no cistern disassembly




Telescopic
overflow

Flexible



- > Adjustable height
by sliding stirrup, matches
most of the cisterns
of the market




- > Adjustable
small flush
with notches



- > Lid hole:
from 18 to 50 mm



- > Buttons:
easily adjustable



- > Deadwater level:
preset and adjustable
on some items

- > Innovation:
very quiet
and water saving

ULTRA QUIET
< 10 dB



For more information:
Web: siamp.co.uk

> Features

Inlet valves		95 OD	Compact 95L	Compact 99T BP	Compact OD 99T BP	Compact 99B	Compact OD 99BP
Entry	Side	•	•				
	Bottom			•	•	•	•
Closure	Hydraulic	•	•	•	•	•	•
	Mechanical						
Connection	3/8" brass	•	•	•			
	1/2" brass		•	•	•		
	1/2" plastic		•	•		•	•
Dimensions	Length (mm)	112	112	75,5	92	75,5	92
	Width (mm)	69	50	53	66	53	66
	Height (from connection axis) (mm)	256	250	235 ~ 344	240 ~ 330	282	284
	Range of settings (mm)	90	105			105	
Certifications	NF	•	•			•	
	DIN		•				
	KIWA		•			•	
	WATERMARK					•	
	WRAS		•	•	•	•	•
Guarantee (years)		10	10	10	10	10	10

Flush valves		Optima S	Optima 50	Optima 49	Skipper 45	Storm 33A
Actuation system	Dual flush	•	•	•	•	
	Single flush					•
Adjustability	Ø Lid hole (mm)	16~50	16~50	16~50	40~44	18~50
	Cistern height (mm)	282~432	272~480	285~448	305~455	305~415
	Overflow height (mm)	185~325	149~245	155~245	180~240	180~240
Certifications	NF	•	•	•	•	•
	WRAS	•	•	•	•	•
Guarantee (years)		10	10	10	10	10

> Hydraulic with delayed action 95 OD




DESCRIPTION

- > Ultra quiet : 16 times more quiet than a traditional inlet valve
- > The delayed action opening case delays the filling of the cistern while the flush valve is open
- > Can be installed into ceramic or plastic cisterns, recessed or low level, for replacement or as original equipment
- > Compact
- > Hydraulic closure (no water hammer shock)
- > Adjustable water level
- > Anti-backflow function
- > Nickel coated 3/8" brass end-fitting
- > Flow rate: 0.12 l/s at 3 bars
- > Pressure function range: from 0.5 to 12 bars

DELAYED ACTION MECHANISM



The cistern empties quicker than the water in the delaying case, keeping the inlet valve closed.



A case full of tiny marbles reduces the water pressure that comes through the inlet. This reduced flow makes the inlet ultra quiet.



Once the flush is complete and the flush valve closes, the delaying case keeps draining water which then allows, the inlet valve open and refill the cistern.

TEXT FOR TENDERS:


95 OD

Ref.: 30 7781 10

Side entry inlet valve with 3/8" brass connection, NF certified and 10-year-warranty.

Features: ultra quiet and water saving, hydraulic closure, adjustable water level and anti-back flow. Length 256mm, width 112mm, depth 69mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
95 OD	30 7781 10	3 24723 007126 5	Box	20	0.08	7.08	300



*Based upon a 4-people-family consumption when replacing a standard inlet valve



For more information:
Web: siamp.co.uk

> Hydraulic COMPACT 95L




HYDRAULIC
CLOSURE



AVAILABLE IN
1/2" AND 3/8"
BRASS

DESCRIPTION

- > Compact
- > Can be installed into ceramic or plastic cisterns, recessed or low level cisterns, for replacement or as original equipment
- > Hydraulic closure (no water hammer shock)
- > Adjustable water level
- > Quiet
- > Anti-backflow function
- > Filter can be reached without disconnecting from water supply
- > 1/2" plastic, 1/2" & 3/8" brass end-fitting
 - 1/2" plastic:
 - flow rate : 0.14l/s at 3 bars
 - Pressure function range from 0.5 to 10 bars
 - 1/2" brass:
 - flow rate : 0.14l/s at 3 bars
 - Pressure function range from 0.5 to 10 bars
 - 3/8" brass :
 - flow rate : 0.13l/s at 3 bars
 - Pressure function range from 0.5 to 10 bars



TEXT FOR TENDERS:

COMPACT 95L WRAS NF

Side entry inlet valve with 1/2" & 3/8" brass connection 1/2" plastic, WRAS and NF certified and 10-year-guarantee.

Features : quiet, hydraulic closure, adjustable water level and anti-back flow. Maintenance without the need for full disassembly. Length 270mm, width 112mm, depth 50mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
COMPACT 95L 1/2" plastic	30 9506 07	3 24723 001493 4	Bag	50	0.08	14.5	750
COMPACT 95L 1/2" & 3/8" brass	30 9565 10	3 24723 007068 8	Box	24	0.08	9.6	360

> Hydraulic COMPACT 99T BP




TELESCOPIC



AVAILABLE IN
1/2" AND 3/8"
BRASS

DESCRIPTION

- Low pressure
- Compact with telescopic adjustment
- Can be installed into ceramic or plastic cisterns, recessed or low level cisterns, for replacement or as original equipment
- Hydraulic closure (no water hammer shock)
- Adjustable water level
- Quiet
- Anti-backflow function
- 3/8" brass, 1/2" brass and 1/2" plastic end-fitting:
 - 3/8" brass :
 - flow rate : 0.21l/s at 3 bars
 - Pressure function range from 0.1 to 10 bars
 - 1/2" brass :
 - flow rate : 0.23l/s at 3 bars
 - Pressure function range from 0.1 to 10 bars
 - 1/2" plastic :
 - flow rate : 0.22l/s at 3 bars
 - Pressure function range from 0.1 to 10 bars



TEXT FOR TENDERS:

COMPACT 99T BP WRAS

Bottom entry inlet valve available with 1/2" & 3/8" brass connection 1/2" plastic, WRAS certified 10-year-guarantee.

Features: adjustable height, low pressure, quiet, hydraulic closure, adjustable water level and anti-back flow. Length 270mm, width 112mm, depth 50mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
COMPACT 99T BP Low Pressure 3/8" Brass	30 9922 10	3 24723 00695 38	Box	24	0.08	8.5	360
COMPACT 99T BP Low Pressure 1/2" Plastic telescopic	30 9980 10	3 24723 00712 72	Box	24	0.08	8	360
COMPACT 99T BP Low Pressure 1/2" Brass	30 9921 10	3 24723 00695 21	Box	24	0.08	8.5	360



For more information:
Web: siamp.co.uk

> Hydraulic COMPACT OD 99T BP




DESCRIPTION

- > Delayed action
- > Low pressure
- > Compact with telescopic adjustment
- > Can be installed into ceramic or plastic cisterns, recessed or low level cisterns, for replacement or as original equipment
- > Hydraulic closure (no water hammer shock)
- > Adjustable water level
- > Quiet
- > Anti-backflow function
- > From 0.1 to 10 bar
- > Flow rate 0.23l/s at 3 bars
- > 1/2" brass

DELAYED ACTION MECHANISM



The cistern empties quicker than the water in the delaying case, keeping the inlet valve closed.



Once the flush is complete and the flush valve closes, the delaying case keeps draining water which then allows the inlet valve open and refill the cistern.


TEXT FOR TENDERS:

COMPACT OD 99T BP WRAS

Bottom entry inlet valve with 1/2" brass connection WRAS certified and 10-year-guarantee. Features: delayed action, adjustable height, low pressure, quiet, hydraulic closure, adjustable water level and anti-back flow. Length 270mm, width 112mm, depth 50mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
COMPACT OD 99T BP Low Pressure 1/2" Brass Delayed Action	30 9923 10	3 24723 006954 5	Box	24	0.08	9.7	360

*Based upon a 4-people-family consumption when replacing a standard inlet valve




> Hydraulic COMPACT 99B



DESCRIPTION

- Compact
- Can be installed into ceramic or plastic cisterns, for replacement or as original equipment
- Hydraulic closure (no water hammer shock)
- Adjustable water level
- Quiet
- Anti-backflow function
- Flow from 0.15l/s at 3 bars
- From 0.5 to 10 bar



TEXT FOR TENDERS:

COMPACT 99B WRAS

Bottom entry inlet valve with connection 1/2" plastic, WRAS certified and 10-year-guarantee. Features: quiet, hydraulic closure, adjustable water level and anti-back flow. Length 270mm, width 112mm, depth 50mm.


	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
COMPACT 99B 1/2" Plastic	30 9960 07	3 24723 001282 4	Bag	60	0.08	18.8	900



For more information:
Web: siamp.co.uk

> Hydraulic with delayed action

COMPACT OD 99BP




DESCRIPTION

- > Low pressure
- > 99 OD saves water by delaying cistern filling while flush valve is opened
- > Compact
- > Can be installed into ceramic or plastic cisterns, for replacement or as original equipment
- > Hydraulic closure (no water hammer shock)
- > Adjustable water level
- > Quiet
- > Anti-backflow function
- > 1/2" plastic connection
- > Flow rate: 0.22l/s at 3 bars
- > Pressure function range: 0.1 to 10 bar

DELAYED ACTION MECHANISM



The cistern empties quicker than the water in the delaying case, keeping the inlet valve closed.



Once the flush is complete and the flush valve closes, the delaying case keeps draining water which then allows the inlet valve open and refill the cistern.

TEXT FOR TENDERS:


COMPACT OD 99BP WRAS

Bottom entry inlet valve with 1/2" plastic connection, NF and WRAS certified and 10-year-guarantee.

Features : delayed action, low pressure, quiet, hydraulic closure, adjustable water level and anti-back flow. Length 284mm, width 92mm, depth 66mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
COMPACT OD 99BP Low pressure 1/2" plastic Delayed Inlet Valve	30 9911 07	3 24723 006954 5	Box	24	0.08	8.75	360

*Based upon a 4-people-family consumption when replacing a standard inlet valve



> Adjustable siphon UNISIPHON




DESCRIPTION

- > To be installed into plastic or ceramic cisterns
- > One adjustable height siphon for replacing many of the current specific height ones
- > Adjustable height from 7 1/2" (248mm.) to 9 1/2" (290mm.)
- > Featuring overflow
- > Adjustable flush volume
- > Adjustable dead water level
- > 2 part siphon easy to maintain without the need for cistern disassembly

Minimum height

Adjustable overflow height (B):
from 248 to 290 mm Lid inner top

Maximum height




TEXT FOR TENDERS:

UNISIPHON WRAS

Unisiphon can be used as a replacement in many high and low level, lever operated ceramic or concealed cisterns.

Quick servicing : a 2-part design that enables the syphon body to be easily removed from the cistern, leaving the leg plugged.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
UNISIPHON	32 8004 07	3 24723 007197 5	Card topped bag	12	0.08	8	180



For more information:
Web: siamp.co.uk

> Dual flush telescopic OPTIMA S



DESCRIPTION

- Can be installed into ceramic or plastic cisterns, for replacement or as original equipment
- Push button: dual flush
- Actuation effort below 20 Newton
- For lid holes ranging from 16 to 50mm, with or without collar depending on the diameter
- Button off-center +/- 15mm
- Stirrup: adjustable in increments of 10 mm
- Adjustable overflow, in increments of 10mm
- Adjustable small flush, from 2l to 4.5l (no cutting required)
- Adjustable deadwater level up to 60 mm
- High flush rate of 3.5l/s
- Foam pan seal supplied for compensating pan irregularity



**RAISED BUTTON
AVAILABLE**
(see page 55
for more details)

Optima S flush
valve available in
a pack with the
Delayed Action
99T BP inlet valve




Compatible with:

- Lid hole Ø (A) from 16 to 50mm
- Drainage hole Ø (D) from 58 to 72mm

Adjustable height (B):

- With collar: from 282 to 432mm (lid hole Ø ranging from 16 to 38mm and 43 to 50mm)
- Without: from 300 to 445mm (lid hole Ø ranging from 39 to 42mm)

Adjustable telescopic overflow height (C): 185 to 325mm



TEXT FOR TENDERS:

OPTIMA S WRAS NF

Dual flush valve NF and WRAS certified, compact and water saving. The stirrup fixes the cistern lid once the button is screwed down and enables a non alignment position. Adjustable button with optional collar.

Adjustable height from 282 and 432 mm, lid hole from 16 to 50, discharge hole from 58 to 72 mm. Adjustable : small flush, over flow (with no cut), dead water level.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
OPTIMA S	32 7004 10	3 24723 009267 3	Box	14	0.08	9	210
OPTIMA S/99T BP 1/2" Brass OD deluxe component pack	37 9411 10	3 24723 009146 1	Box	9	0.08	9.2	135
Optima S raised button	34 7051 07	3 24723 004273 9	Bag	250	0.07	12.5	-

SIAMP

> Dual flush telescopic OPTIMA 49




DESCRIPTION

- Can be installed into plastic or ceramic cisterns
- Push button: dual flush
- Actuation effort below 20 Newton
- For lid holes ranging from Ø 16 to 50mm, with or without collar depending on the diameter
- Button off-center +/- 15mm
- Stirrup : adjustable in increments of 12mm
- Overflow can be cut in increments of 4mm
- Adjustable small flush from 2l to 4.5l
- Adjustable dead water level
- High flush rate of 3.5l/s
- Foam pan seal supplied for compensating pan irregularity



**RAISED BUTTON
AVAILABLE
(see page 55
for more details)**

- Adjustable height (B):
- With collar: from 282 to 430mm (lid hole Ø ranging from 16 to 38mm and 43 to 50mm)
 - Without: from 300 to 448mm (lid hole Ø ranging from 39 to 42mm)
- Adjustable overflow height (C): 155 to 245mm
- Compatible with:
- Lid hole Ø (A) from 16 to 50mm
 - Drainage hole Ø (D) from 58 to 72mm



TEXT FOR TENDERS:

OPTIMA 49 WRAS NF

Dual flush valve WRAS and NF certified, compact and water saving. The stirrup fixes the cistern lid once the button is screwed down and enables a non alignment position. Adjustable button with optional collar.


Adjustable height from 282 and 430 mm, lid hole from 16 to 50, discharge hole from 58 to 72 mm. Adjustable : small flush, over flow, dead water level.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
OPTIMA 49	32 4999 10	3 24723 007129 6	Box	14	0.08	9	210
Optima 49 raised button	34 5054 07	3 24723 004328 6	Bag	250	0.07	12.5	-



For more information:
Web: siamp.co.uk

> Dual flush with cable OPTIMA 50



DESCRIPTION

- > Can be installed into plastic or ceramic cisterns
- > Push button: dual flush
- > Actuation effort below 20N
- > For lid holes ranging from 16 to 50mm, with or without collar depending on diameter
- > Cable operated: allows an actuation at distance, lateral or head-on position
- > Over flow can be cut in increments of 4mm
- > Adjustable small flush from 2l to 4.5l
- > Adjustable dead water level
- > High flush rate of 3.5l/s
- > Foam pan seal supplied for compensating pan irregularity



**RAISED BUTTON
AVAILABLE
(see page 55
for more details)**




**Optima 50 flush
valve available in a
pack with the 99B
inlet valve**



**Optima 50 flush
valve available in a
pack with the 99T BP
inlet valve**

Compatible with:
- Lid hole (A), Ø from
16 to 50mm
- Drainage hole (D) Ø
from 58 to 72mm

Adjustable height (B)
- With collar:
from 272 to 480mm
(Lid hole (A) Ø 18 to 37mm and >
than 44mm)
- Without: from 287 to 480mm
(Lid hole A, Ø 38 to 44mm)
Adjustable overflow height:
from 149 to 245mm (C)



TEXT FOR TENDERS:

OPTIMA 50

Dual flush valve NF and WRAS certified, compact, water saving and cable operated. It allows an actuation at distance, lateral or head-on. Adjustable button with optional collar. Adjustable height from 272 and 482 mm, lid hole from 16 to 50, discharge hole from 58 to 72 mm. Adjustable : small flush, over flow, dead water level.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
OPTIMA 50 Cable L495mm	32 5002 10	3 24723 007130 2	Box	14	0.08	7.6	210
OPTIMA 50/99B 1/2" plastic component pack	37 9980 07	3 24723 002373 8	Bag	16	0.08	13.2	240
OPTIMA 50/99T BP 1/2" brass deluxe component pack	37 9981 10	3 24723 007128 9	Box	9	0.08	8.75	135
Optima 50 Raised Button	34 5051 07	3 24723 004274 6	Bag	250	0.07	12.5	-

> Dual flush SKIPPER 45



DESCRIPTION

- > Can be installed into plastic or ceramic cisterns
- > Push button: dual flush
- > Actuation effort below 20 Newton
- > For lid holes ranging from 40 to 44mm
- > Over flow can be cut in increments of 5mm
- > Adjustable small flush from 2l to 4.5l
- > High flush rate of 3.5l/s
- > Foam pan seal supplied for compensating pan irregularity




Skipper 45 flush valve available in a pack with the 99B inlet valve

Compatible with:

- Lid hole (A), Ø from 40 to 44mm
- Drainage hole (D) Ø from 72mm

Adjustable height (B) from 305mm min to 455 mm max.

Adjustable overflow height: from 180 to 240mm (C)



TEXT FOR TENDERS:

SKIPPER 45 WRAS NF

Dual flush valve NF and WRAS certified, compact. 10 year guarantee. The stirrup fixes the cistern lid, once the button is screwed down and enables a non-alignment position. Adjustable height from 305 and 455 mm, lid hole from 16 to 50, discharge hole from 58 to 72 mm. Adjustable : small flush, over flow, dead water level.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
SKIPPER 45	32 4560 10	3 24723 007132 6	Box	14	0.08	7.05	210
SKIPPER 45/99B 1/2P component pack	33 9950 07	3 24723 007142 5	Bag	15	0.08	10.25	225



For more information:
Web: siamp.co.uk

> Single flush STORM 33A



DESCRIPTION

- Can be installed into plastic or ceramic cisterns
- Single flush, full cistern discharge
- Actuation effort below 20 Newton
- For lid holes ranging from 18 to 50mm, with or without collar depending on diameter
- Adjustable stirrup that fixes the cistern lid and enables a non alignment position
- Overflow can be cut in increments of 5mm
- High flush rate of 3.5l/s
- Foam pan seal supplied for compensating pan irregularity



Storm 33A flush valve available in a pack with the 99B inlet valve


Compatible with:

- Lid hole (A), Ø 18 to 50mm
- Drainage hole (D) Ø from 58 to 72mm

Adjustable height (B):

- With collar: from 305 to 339mm (Lid hole (A) Ø 18 to 38mm)
- Without: from 321 to 415mm (Lid hole A, Ø 39 to 42mm)

Adjustable overflow height: 180 to 240mm (C)



TEXT FOR TENDERS:

STORM 33A WRAS NF

Single flush valve WRAS and NF certified, 10-year-guarantee. The stirrup fixes the cistern lid, once the button is screwed down and enables a non-alignment position. Adjustable button and optional collar.

Adjustable height from 305 and 415 mm, lid hole from 16 to 50, discharge hole from 58 to 72 mm. Adjustable over flow.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
STORM 33A	32 3355 10	3 24723 007131 9	Box	14	0.08	7	210
STORM 33A/99B 1/2P component pack	35 9950 07	3 24723 007143 2	Bag	15	0.08	11.75	225

> TOILET SEATS

Wall frames

Concealed cisterns

Flushing options

Wall solutions accessories

Technical equipment

Toilet seats





> TOILET SEATS


Toilet seat manufacturing has been an integral part of SIAMP's business since its founding in 1947.

> **THE VARIOUS MATERIALS OF OUR TOILET SEATS:**


- **THERMOPLASTIC:** economical, hard wearing and made with recyclable material.
- **THERMOSET:** heavy duty, manufactured with high quality antibacterial and scratch-resistant materials.
- **MDF:** medium-density fibreboard, with the aesthetics and warmth of wood.
- **COMPOSITE WOOD:** the most robust material, dedicated to luxury products, offering a high quality finish.

> **HINGE OPTIONS:**

- **PREMIUM:** Quick fitting, soft close and detachable. Designed for both comfort and hygiene.
- **CLASSIC:** Products intended for intensive use, especially in commercial projects.



> Features

TOILET SEATS		CAP FERRAT Premium	CAP FERRAT Classic	HORIZON	ESTÉREL Premium	ESTÉREL Classic	PRINCIPAUTE Premium	GÉNÉRATIONS Premium	OPIO Premium	OPIO Classic	MONTE CARLO 3
Material	Thermoplastic							•	•	•	•
	Thermoset				•	•	•				
	MDF			•							
	Composite wood	•	•								
Fixing system	Plate + plastic screw quick fitting										•
	Individual hinge, stainless steel	inox	inox			inox			inox	inox	
	Top fixing	•	•		•		•	•			
Comfort	Soft close	•			•		•	•	•		
	Antibacterial	•	•		•	•	•				
	Quick release	•			•		•		•		
Shape	Oval	•	•	•	•	•		•	•	•	•
	D-shape						•				
Dimensions	Length (en mm)	426	426	425	450	449	433	447	422,5	422,5	435
	Width (in mm)	380	380	370	376	369	368	371	367	367	364
	Center distance WC (in mm)	120 ~ 180	120 ~ 180	110 ~ 200	80 ~ 175	155	80 ~ 175	95 ~ 185	130 ~ 180	130 ~ 165	133 ~ 180
	Opening angle	98°	98°	98°	110°	110°	110°	98°	98°	98°	98°
Weight		2,8	2,8	2,8	2,3	1,6	2,5	1,9	1,7	1,7	1,35
Guarantee (years)		5	5	1	2	2	2	2	2	2	2
		•	•			•			•	•	•



> Toilet seat / Composite wood CAP FERRAT CLASSIC





COMPOSITE WOOD



DESCRIPTION

- Fits all standard WC
- Composite wood : robust material
- Anti-bacterial
- 2.8 kg
- Hard wearing*
- Stainless-steel hinges
- Top fixing




TEXT FOR TENDERS

CAP FERRAT CLASSIC

Ref. : 95 9500 10

Lacquered composite wood toilet seat, hard-wearing, 5-year guarantee, anti-bacterial, white, 2.8 kg. Dimensions L 426 mm and l 380 mm, opening angle 98°. Fits all standard WC having fixing dimensions from 120 to 180 mm. Top fixing stainless steel hinges.



- A - Fixing centers 120-180mm
- B - Width 380 mm
- C - WC length 440-460
- D - Ring inner dimensions:
Maximum length 287 mm
Maximum width 235 mm
- E - Opening angle 98°

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
CAP FERRAT CLASSIC	95 9500 10	3 24723 007672 7	Box	5	0.06	17.5	150

*under normal conditions of use

SIAMP

> Toilet seat soft close / Composite wood CAP FERRAT PREMIUM





COMPOSITE WOOD



DESCRIPTION

- Fits all standard WC
- Composite wood : robust material
- Soft closing hinges
- Quick release : easy to clean
- Anti-bacterial
- 2.8 kg
- Hard wearing*
- Stainless-steel hinges
- Top fixing




TEXT FOR TENDERS

CAP FERRAT PREMIUM

Ref. : 95 9501 10

Lacquered composite wood toilet seat, hard-wearing, 5-year guarantee, anti-bacterial, white, 2.8 kg. Dimensions L 426 mm and l 380 mm, opening angle 98°. Fits all standard WC having fixing dimensions from 120 to 180 mm. Top fixing stainless steel hinges. Soft closing hinges and quick release.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
CAP FERRAT PREMIUM	95 9501 10	3 24723008739 6	Box	5	0,06	17.5	155

*under normal conditions of use



For more information:
Web: siamp.co.uk

> Toilet seat / MDF HORIZON CLASSIC



DESCRIPTION

- Fits all standard WC
- MDF
- 2.8kg
- Anti-UV treatment, water resistant
- Metallic hinges and screws

Material:
MDF, resistant to usual
household products and scratch

Lid:
Thickness 15 mm

Buffers:
- 4 seat ring buffers
- 2 cover buffers

Seat:
Thickness 18 mm


Metallic hinges and screws



TEXT FOR TENDERS

HORIZON CLASSIC Ref. : 95 8270 10

MDF toilet seat, 1-year guarantee, white, 2.7 kg. Dimensions L425mm and I370 mm, opening angle 98°. Fits all standard WC having fixing centers dimensions from 110 to 200 mm, metallic and adjustable hinges and screws.



	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
HORIZON CLASSIC	95 8270 10	3 24723008342 8	Box	1	0,012	3,5	144


> Toilet seat soft close / Thermoset ESTÉREL PREMIUM

- Quick fitting
- Soft closing hinges
- Quick release




DESCRIPTION

- Fits all standard WC
- Anti-bacterial
- Thermoset
- 2.3kg
- Scratch resistant
- Top fixing
- Individual and adjustable stainless steel hinges, with fast-fix screws
- Soft closing hinges
- Quick release: easy to clean



Material:
Anti-bacterial
Thermoset



Buffers:
- 4 seat ring buffers
- 2 cover buffers



Top fixing hinges
Fast-fix screws and
stainless steel cap





TEXT FOR TENDERS

ESTÉREL PREMIUM
Ref. : 95 9003 10

Thermoset toilet seat, 2-year guarantee, Anti-bacterial, white, 2.3 kg. Dimensions L450 mm and I376 mm, opening angle 110°. Fits all standard WC having fixing dimensions from 80 to 175 mm. Top fix stainless steel hinges. Quick release and soft closing seat.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
ESTÉREL PREMIUM	95 9003 10	3 24723 0076437	Box	7	0,08	19,5	168



- A - Fixing centers 80 to 175 mm
- B - Width 376 mm
- C - WC length 420~ 450 mm
- D - Ring inner dimensions:
Maximum length 281 mm
Maximum width 232 mm
- E - Opening angle 110°



For more information:
Web: siamp.co.uk

> Toilet seat / Thermoset ESTÉREL CLASSIC



DESCRIPTION

- Fits all standard WC
- Thermoset
- Anti-bacterial
- 1.6kg
- Scratch resistant
- Individual stainless steel hinges




TEXT FOR TENDERS

ESTÉREL CLASSIC Ref. : 95 9002 10

Thermoset toilet seat, 2-year guarantee, anti-bacterial, white, 1.6 kg. Dimensions L449 mm and l369 mm, opening angle 110°. Fits all standard WC having fixing dimensions from 95 to 185 mm. Individual stainless steel hinges.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
ESTÉREL CLASSIC	95 9002 10	3 24723 0076420	Box	4	0,05	9,2	160




> Toilet seat soft close / Thermoset PRINCPAUTÉ PREMIUM



DESCRIPTION

- Wrapover and D-Shape design
- Anti-bacterial
- Thermoset
- 2.5kg
- Scratch resistant
- Top fixing
- Individual and adjustable stainless steel hinges, with fast-fix screws
- Soft closing hinges
- Quick release: easy to clean




TEXT FOR TENDERS

PRINCPAUTÉ PREMIUM

Ref: 95 9001 10

Duroplast toilet seat, 2-year guarantee, anti-bacterial, white, 2.5 kg. Dimensions L433 mm and I368 mm, opening angle 110°. Fits all D-shaped WC having fixing dimensions from 80 to 175 mm. Individual and adjustable stainless steel hinges, with fast-fix screws. Quick release and soft closing seat.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
PRINCPAUTÉ PREMIUM	95 9001 10	3 24723 0076413	Box	4	0.05	13.2	160



For more information:
Web: siamp.co.uk



> Toilet seat soft close / Thermoplastic GENERATIONS PREMIUM

REMOVABLE
CHILDREN SEAT



DESCRIPTION

- > Fits all standard WC
- > Removable children seat
- > Thermoplastic
- > 1,9 kg
- > Hard wearing*
- > Soft closing hinges
- > Quick release: easy to clean
- > Individual and adjustable stainless steel hinges, with fast-fix screws



TEXT FOR TENDERS


GÉNÉRATIONS PREMIUM

Ref.: 95 8223 10

Toilet seat in thermoplastic, including a removable children seat, 2-year guarantee, white, 1.9kg. Dimensions L447mm and l371mm, opening angle 98°. Fits all standard WC with fixing dimensions from 95 to 185mm, top fix and stainless steel hinges, quick release and soft closing seat.


	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
GENERATIONS PREMIUM	95 8223 10	3 24723 007665 9	Box	5	0.07	12.5	120

*under normal conditions of use



> Toilet seat soft close / Thermoplastic OPIO PREMIUM

**SOFT CLOSING HINGES
QUICK RELEASE**




DESCRIPTION

- Fits all standard WC
- Thermoplastic
- Soft closing hinges
- Quick release: easy to clean
- 1.7 kg
- Hard wearing*
- Metal hinges with plastic cover caps
- Available in white



Material:
anti-static
polypropylene



Buffers:
- 4 seat ring buffers
- 2 cover buffers

Individual and soft closing polyamide
hinges and adjustable,
with metal fixing screws


TEXT FOR TENDERS

OPIO PREMIUM
REF.: 47 1055 10

Toilet seat in thermoplastic, 2-year guarantee, white, 1.7 kg. Dimensions L 422.5 mm and I 367 mm, opening angle 98°. Fits all standard WC having fixing dimensions from 130 to 180 mm. Individual and soft closing hinges, quick release and adjustable, with metal fixing screws

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
OPIO PREMIUM	47 1055 10	3 24723 003075 0	Tray	6	0,07	13,2	144

*under normal conditions of use



- A - Fixing centers 130-180mm
- B - Width 367 mm
- C - WC length 405-450mm
- D - Ring inner dimensions:
Maximum length 258 mm
Maximum width 215 mm
- E - Opening angle 98°




For more information:
Web: siamp.co.uk

> Toilet seat / Thermoplastic OPIO CLASSIC



DESCRIPTION

- > Fits all standard WC
- > Thermoplastic
- > 1.7 kg
- > Hard wearing*
- > Stainless steel top-fixing screws, centering and anti-slip soles




TEXT FOR TENDERS

OPIO CLASSIC Ref: 47 1056 10

Toilet seat in thermoplastic, 2-year guarantee, white, 1.7 kg. Dimensions L 422.5 mm and I 367 mm, opening angle 98°. Fits all standard WC having fixing dimensions from 130 to 165 mm. Individual and adjustable stainless steel hinges.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M³	Kg	
OPIO CLASSIC	47 1056 10	3 24723 001697 6	Tray	6	0,07	13,02	144

*under normal conditions of use




> Toilet seat / Thermoplastic MONTE-CARLO 3 RANGE



DESCRIPTION

- Universal design adapted to fit majority of standard WCs
- Thermoplastic
- 1,35 kg
- Hard wearing*
- Adjustable bar hinge and plastic screw, quick fixing
- Available in white and colours:
 - Anthracite
 - Manhattan grey
 - Dark Grey
 - Rapsberry
 - Plum
 - Green
 - Taupe




TEXT FOR TENDERS

MONTE-CARLO 3 NF

Toilet seat in thermoplastic, NF certified, 2-year warranty. Dimensions : 435mm length, 364mm width, opening angle of 98°. Fits majority of standard WC with fixing dimensions from 133 to 180mm.

	Ref.	Barcode	Packing	Packing			Pallet quantity
				Nb	M ³	Kg	
MONTE CARLO 3 White	45 5251 18	3 24723 003557 1	Tray	10	0,134	17,89	160
MONTE CARLO 3 Anthracite	45 5253 18	3247230050284	Tray	10	0,134	17,89	160
MONTE CARLO 3 Manhattan grey	45 5254 18 0096	3247230053742	Tray	3	0,043	5,55	108
MONTE CARLO 3 Dark grey	45 5254 18 1480	3247230051885	Tray	3	0,043	5,55	108
MONTE CARLO 3 Rapsberry	45 5254 18 6773	3247230051892	Tray	3	0,043	5,55	108
MONTE CARLO 3 Plum	45 5254 18 0639	3247230051861	Tray	3	0,043	5,55	108
MONTE CARLO 3 Green	45 5254 18 2972	3247230051878	Tray	3	0,043	5,55	108
MONTE CARLO 3 Taupe	45 5254 18 6056	3247230051908	Tray	3	0,043	5,55	108



- A - Fixing centers 133-180mm
- B - Width 364 mm
- C - WC length 405-450
- D - Ring inner dimensions:
 - Maximum length 280 mm
 - Maximum width 225 mm
- E - Opening angle 98°

*under normal conditions of use



For more information:
Web: siamp.co.uk


> Toilet seat / Thermoplastic
MONTE-CARLO 3 COLOURS




Dark grey



Green



Plum



Raspberry



Manhattan grey



Taupe



Anthracite

> Measures, weights and pressures conversion table

Linear measures		
1 millimetre	mm	0,03937 inch
1 centimetre	cm	0,3937 inch
1 metre	m	39,37 inches
1 metre	m	3,2808 feet
1 metre	m	1,0936 yards

Square measures		
1 square centimetre	cm ²	0,155 square inch
1 square metre	m ²	10,764 square feet
1 square metre	m ²	1,196 square yards

Cubic measures		
1 cubic centimetre	cm ³	0,061 cubic inch
1 cubic metre	m ³	35,315 cubic feet
1 cubic metre	m ³	1,308 cubic yards
1 cubic metre	m ³	1000 litres

Measures of capacity		
		UK
1 litre	l	1,76 pints
1 litre	l	0,22 gallon
		US
1 litre	l	2,11 pints
1 litre	l	0,264 gallon

Weights		
1 gram	g	15,4 grains
1 kilogram	kg	2,2046 pounds
1 quintal	q	220,46 pounds

Pressures		
1 bar	bar	100 kpa
1 bar	bar	14,5 psi
1 bar	bar	1,02 kg/cm ²
1 bar	bar	10,2 water meter



> Index

Ref.	Désignation	Pages	Ref.	Désignation	Pages
30			32		
30 7781 10	95 OD	62	32 3355 10	STORM 33A	73
30 9506 07	COMPACT 95L 1/2" plastic	63	32 4560 10	SKIPPER 45	72
30 9565 10	COMPACT 95L 1/2" & 3/8" brass	63	32 4999 10	OPTIMA 49	70
30 9911 07	COMPACT OD 99BP Low pressure 1/2" plastic Delayed Inlet Valve	67	32 5002 10	OPTIMA 50 Cable L495mm	71
30 9921 10	COMPACT 99T BP Low Pressure 1/2" Brass	64	32 7004 10	OPTIMA S	69
30 9922 10	COMPACT 99T BP Low Pressure 3/8" Brass	64	32 8004 07	UNISIPHON	68
30 9923 10	COMPACT OD 99T BP Low Pressure 1/2" Brass Delayed Action	65	33		
30 9960 07	COMPACT 99B 1/2" Plastic	66	33 9950 07	SKIPPER 45/99B 1/2P component pack	72
30 9980 10	COMPACT 99T BP Low Pressure 1/2" Plastic telescopic	64	34		
31			34 1064 07	Corner fixing top brackets	56
31 0144 11	INTRA PNEUMATIC Bottom inlet	34	34 1065 07	Corner fixing WC brackets	56
31 0147 10	INTRA CABLE Bottom inlet	31	34 1149 46	Extended flush plate fixing screws	57
31 0147 18	TRUEFLOW Bottom inlet	35	34 1151 07	Extended rods	57
31 0148 10	INTRA CABLE Side inlet	32	34 5051 07	Optima 50 Raised Button	55, 69
31 0150 10	INTRA CABLE ECO Bottom inlet	30	34 5054 07	Optima 49 Raised Button	70
31 0154 10	INTRA PNEUMATIC ECO Bottom inlet	33	34 7051 07	Optima S raised button	70
31 1167 10	BCM 800	18	35		
31 1250 10	BLM 400	21	35 9950 07	STORM 33A/99B 1/2P component pack	73
31 1690 10	ALBUM 90 Natural Oak / Bright chrome	40	37		
31 1691 10	ALBUM 90 Stone Grey / Bright chrome	40	37 9411 10	OPTIMA S/99T BP 1/2" Brass OD deluxe component pack	69
31 1692 10	ALBUM 90 Black / Bright chrome	40	37 9980 07	OPTIMA 50/99B 1/2" plastic component pack	71
31 1710 10	SEGMENT White / Bright chrome inserts	44	37 9981 10	OPTIMA 50/99T BP 1/2" brass deluxe component pack	71
31 1711 10	SEGMENT Black / Bright chrome inserts	44	45		
31 1712 10	SEGMENT Stainless steel finish / Bright chrome inserts	44	45 5251 18	MONTE CARLO 3 White	86
31 1722 10	SEGMENT Bright chrome / Matt chrome inserts	44	45 5253 18	MONTE CARLO 3 Anthracite	87
31 1790 10	ALBUM 360 Natural Oak / Bright chrome	39	45 5254 18 0096	MONTE CARLO 3 Manhattan grey	87
31 1791 10	ALBUM 360 Stone Grey / Bright chrome	39	45 5254 18 0639	MONTE CARLO 3 Plum	87
31 1792 10	ALBUM 360 Black / Bright chrome	39	45 5254 18 1480	MONTE CARLO 3 Dark grey	87
31 1800 10	YIN YANG White	47	45 5254 18 2972	MONTE CARLO 3 Green	87
31 1813 10	LEMON Matt chrome	48	45 5254 18 6056	MONTE CARLO 3 Taupe	87
31 1814 10	LEMON Bright chrome	48	45 5254 18 6773	MONTE CARLO 3 Rapsberry	87
31 1850 10	YIN YANG Matt chrome / Bright chrome	47	47		
31 1853 10	YIN YANG Bright chrome / Matt chrome	47	47 1055 10	OPIO PREMIUM	84
31 1853 16	YIN YANG Bright chrome	47	47 1056 10	OPIO CLASSIC	85
31 1858 15	WC pack STANDARD SAMOA	25	92		
31 1872 10	SMART Clear matt chrome & Vandal resistant / Fingerprints proof	45	92 0145 07	Long supply sleeve straight connector	57
31 1874 10	SMART Bright chrome & Vandal resistant	45	92 3060 52	100-110mm Adapter R110	57
31 1888 10	Monovolume anti-vandal single flush, stainless steel	49	92 4000 07	Bent drainage set	56
31 1910 10	SMARTY White	46	92 4010 07	Straight drainage set	56
31 1911 10	SMARTY Matt chrome	46	95		
31 1912 10	SMARTY Bright chrome	46	95 8223 10	GENERATIONS PREMIUM	83
31 1931 10	REFLET 90 Black / Matt chrome	42	95 8270 10	HORIZON CLASSIC	79
31 1932 10	REFLET 90 Natural green / Matt chrome	42	95 9001 10	PRINCIPAUTÉ PREMIUM	82
31 1934 10	REFLET 90 White / Matt chrome	42	95 9002 10	ESTÉREL CLASSIC	81
31 1950 10	SMART MVI Matt chrome	50	95 9003 10	ESTÉREL PREMIUM	80
31 1954 10	SMART MVI BATTERY Matt chrome	51	95 9500 10	CAP FERRAT CLASSIC	77
31 1981 10	REFLET 360 Black / Matt chrome	41	95 9501 10	CAP FERRAT PREMIUM	78
31 1982 10	REFLET 360 Natural green / Matt chrome	41			
31 1984 10	REFLET 360 White / Matt chrome	41			
31 2040 10	SQUARE White / Bright chrome inserts	43			
31 2041 10	SQUARE Black / Bright chrome inserts	43			
31 2042 10	SQUARE Stainless steel finish / Bright chrome inserts	43			
31 2072 10	SQUARE Bright chrome / Matt chrome inserts	43			
31 2104 10	BCU 350	20			
31 2315 13	BCM 350	19			
31 2338 10	WC pack DELUXE SAMOA	24			
31 2505 10	SCU 350	21			
31 2535 10	Pneumatic single flush, recessed with raised button, white	54			
31 2551 10	Pneumatic dual flush button, flush fitting, bright chrome	53			
31 2552 10	Pneumatic anti-vandal single flush button, bright chrome and stainless steel	52			
31 2555 10	Pneumatic single flush, recessed with raised button, bright chrome	54			
31 2790 10	BCM 790	17			
31 5004 10	Extended cable flushing dual flush 800/150	55			
31 5005 10	Extended cable flushing dual flush 800/70	55			
31 9032 10	INTRASLIM B	29			

> Notes



For more information:
Web: siamp.co.uk

> Notes

> Notes



For more information:
Web: siamp.co.uk